

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 27.09.2022

Version number 2 (replaces version 1)

Revision: 27.09.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### · 1.1 Product identifier

· Trade name: **DUPLI-COLOR CEMENT LOOK**

· Article number: 521621, 521638

#### · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

#### · Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC9a Coatings and paints, thinners, paint removers

#### · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

· Application of the substance / the mixture Lacquer

#### · 1.3 Details of the supplier of the safety data sheet

##### · Manufacturer/Supplier:

European Aerosols GmbH\*

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@european-aerosols.com

\*Formerly known as Motip Dupli GmbH

· Further information obtainable from: Department Product Safety

#### · 1.4 Emergency telephone number:

Tel.: +49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergency phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland:

Poison center if child has been poisoned: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

### SECTION 2: Hazards identification

#### · 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 27.09.2022

Version number 2 (replaces version 1)

Revision: 27.09.2022

**Trade name: DUPLI-COLOR CEMENT LOOK**

(Contd. of page 1)

**· 2.2 Label elements****· Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

**· Hazard pictograms**

GHS02

**· Signal word Danger****· Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H412 Harmful to aquatic life with long lasting effects.

**· Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

**· Additional information:**

Buildup of explosive mixtures possible without sufficient ventilation.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**· 2.3 Other hazards****· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**· 3.2 Mixtures****· Description:** Mixture of substances listed below with nonhazardous additions.**· Dangerous components:**

CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43	ethanol Flam. Liq. 2, H225 Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	20-<25%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	12.5-<20%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas 1A, H220 Press. Gas (Comp.), H280	12.5-<20%

(Contd. on page 3)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31






















Printing date 27.09.2022

Version number 2 (replaces version 1)

Revision: 27.09.2022

**Trade name: DUPLI-COLOR CEMENT LOOK**

(Contd. of page 2)

EC number: 926-605-8 Reg.nr.: 01-2119486291-36	Hydrocarbons, C6-C7, Isoalkane, Cyclics, <5% <i>n</i> -Hexane  Flam. Liq. 2, H225  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  STOT SE 3, H336	5-<10%
EC number: 920-750-0 Reg.nr.: 01-2119473851-33-xxxx	Hydrocarbons, C7-C9, <i>n</i> -alkanes, isoalkanes, cyclics  Flam. Liq. 2, H225  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  STOT SE 3, H336 EUH066	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8))  Flam. Gas 1A, H220 Press. Gas (Comp.), H280	2.5-<5%
EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, <i>n</i> -alkanes, isoalkanes, cyclics, <5% <i>n</i> -hexane  Flam. Liq. 2, H225  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; STOT SE 3, H336	2.5-<5%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone  Flam. Liq. 2, H225  Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	<2.5%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide  Carc. 2, H351	<2.5%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43	butanone  Flam. Liq. 2, H225  Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	≤0.5%
CAS: 68155-27-1 EINECS: 268-953-7 Reg.nr.: 01-2119493908-18	Amine, C12-18-Alkyl  STOT RE 2, H373  Skin Corr. 1B, H314  Aquatic Acute 1, H400; Aquatic Chronic 1, H410  Acute Tox. 4, H302; STOT SE 3, H335	≤0.5%

**Additional information:**

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.  
For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

GB

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 27.09.2022

Version number 2 (replaces version 1)

Revision: 27.09.2022

**Trade name: DUPLI-COLOR CEMENT LOOK**

(Contd. of page 3)

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.  
Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters -**
- **Protective equipment:** Mouth respiratory protective device.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.  
Keep away from ignition sources.
- **6.2 Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
No special measures required.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

#### 64-17-5 ethanol

WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm

#### 106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm  
Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm  
Carc (if more than 0.1% of buta-1.3-diene)

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 27.09.2022

Version number 2 (replaces version 1)

Revision: 27.09.2022

**Trade name: DUPLI-COLOR CEMENT LOOK**

(Contd. of page 4)

**67-64-1 acetone**

WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm  
Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

**13463-67-7 titanium dioxide**

WEL Long-term value: 10\* 4\*\* mg/m<sup>3</sup>  
\*total inhalable \*\*respirable

**78-93-3 butanone**

WEL Short-term value: 899 mg/m<sup>3</sup>, 300 ppm  
Long-term value: 600 mg/m<sup>3</sup>, 200 ppm  
Sk, BMGV

**· Ingredients with biological limit values:****78-93-3 butanone**

BMGV 70 µmol/L  
Medium: urine  
Sampling time: post shift  
Parameter: butan-2-one

· **Additional information:** The lists valid during the making were used as basis.

**· 8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· **Hand protection** Not required.

· **Material of gloves** Not required.

· **Penetration time of glove material** Not required.

· **Eye/face protection** Not required.

## SECTION 9: Physical and chemical properties

**· 9.1 Information on basic physical and chemical properties****· General Information**

· **Physical state**

Aerosol

· **Colour:**

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

Not applicable, as aerosol.

· **Flammability**

Not applicable.

· **Lower and upper explosion limit**

· **Lower:**

1.5 Vol % (106-97-8 butane (containing < 0,1 % butadiene (203-450-8)))

· **Upper:**

15 Vol % (64-17-5 ethanol)

· **Flash point:**

Not applicable, as aerosol.

· **Ignition temperature:**

201 °C (393.8 °F) (Hydrocarbons, C6-C7, Isoalkane, Cyclics, <5% n-Hexane)

(Contd. on page 6)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 27.09.2022

Version number 2 (replaces version 1)

Revision: 27.09.2022

**Trade name: DUPLI-COLOR CEMENT LOOK**

(Contd. of page 5)

· <b>Decomposition temperature:</b>	Not determined.
· <b>pH</b>	Mixture is non-soluble (in water).
· <b>Viscosity:</b>	
· <b>Kinematic viscosity</b>	Not determined.
· <b>Dynamic:</b>	Not determined.
· <b>Solubility</b>	
· <b>water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
· <b>Vapour pressure at 20 °C (68 °F):</b>	8300 hPa (6225.5 mm Hg) (74-98-6 propane)
· <b>Density and/or relative density</b>	
· <b>Density:</b>	Not determined.
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.

· <b>9.2 Other information</b>	
· <b>Appearance:</b>	
· <b>Form:</b>	Aerosol
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Explosive properties:</b>	Not determined.
· <b>Solvent content:</b>	
· <b>Organic solvents:</b>	79.1 %
· <b>VOC (EC)</b>	---
	791.0 g/l
· <b>VOC-EU%</b>	79.10 %
· <b>Solids content:</b>	20.4 %
· <b>Change in condition</b>	
· <b>Evaporation rate</b>	Not applicable.

· <b>Information with regard to physical hazard classes</b>	
· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Extremely flammable aerosol. Pressurised container: May burst if heated.
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Void
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 7)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 27.09.2022

Version number 2 (replaces version 1)

Revision: 27.09.2022

**Trade name: DUPLI-COLOR CEMENT LOOK**

(Contd. of page 6)

· **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**· **Acute toxicity**· **LD/LC50 values relevant for classification:****64-17-5 ethanol**

Oral	LD50	10470 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50 / 4h	120 mg/l (rat)

**Hydrocarbons, C6-C7, Isoalkane, Cyclics, <5% n-Hexane**

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50 / 4 h	>20 mg/m3 (rat)

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50 / 4 h	>20000 mg/m3 (rat)

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50 / 4 h	>20 mg/m3 (rat)

**67-64-1 acetone**

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	>15800 mg/kg (rabbit)
Inhalative	LC50 / 4h	76 mg/l (rat)

**78-93-3 butanone**

Oral	LD50	>2193 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	34 mg/m3 (rat)

· **Skin corrosion/irritation** No irritant effect.· **Serious eye damage/irritation** No irritating effect.· **Respiratory or skin sensitisation** No sensitising effects known.· **11.2 Information on other hazards**· **Endocrine disrupting properties**

78-93-3 butanone

List II

### SECTION 12: Ecological information

· **12.1 Toxicity**· **Aquatic toxicity:****64-17-5 ethanol**

LC50/96h	13000 mg/l (oncorhynchus mykiss / Regenbogenforelle)
EC50 / 48 h	12900 mg/l (algae)
LC50 / 48 h	12340 mg/l (daphnia magna)

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 27.09.2022

Version number 2 (replaces version 1)

Revision: 27.09.2022

**Trade name: DUPLI-COLOR CEMENT LOOK**

(Contd. of page 7)

**Hydrocarbons, C6-C7, Isoalkane, Cyclics, <5% n-Hexane**

EC50 / 48 h	3 mg/l (daphnia magna / Wasserfloh)
EC50 / 72 h	30 mg/l (Pseudokirchneriella subcapitata)
LC50 / 96 h	11.4 mg/l (oncorhynchus mykiss / Regenbogenforelle)

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

EC50	50 mg/l (algae)
	5 mg/l (fish)

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

EC50 / 48 h	3 mg/l (daphnia magna / Wasserfloh)
EC50 / 72 h	30 mg/l (Pseudokirchneriella subcapitata)
LC50 / 96 h	11.4 mg/l (oncorhynchus mykiss / Regenbogenforelle)

**67-64-1 acetone**

LC50/96h	8300 mg/l (fish)
EC50/96h	7200 mg/l (algae)
LC50 / 48 h	8450 mg/l (crustacean (water flea))

**78-93-3 butanone**

LC50 / 48 h	308 mg/l (daphnia magna)
LC50 / 72 h	1972 mg/l (Pseudokirchneriella Subcapitata)
LC50 / 96 h	2990 mg/l (fish)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
 Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
 Do not allow product to reach ground water, water course or sewage system.  
 Danger to drinking water if even small quantities leak into the ground.  
 Harmful to aquatic organisms

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation**  
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:**  
 Disposal must be made according to official regulations.  
 Disposal must be made according to official regulations.

**SECTION 14: Transport information**

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1950

(Contd. on page 9)

GB



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 27.09.2022

Version number 2 (replaces version 1)

Revision: 27.09.2022

**Trade name: DUPLI-COLOR CEMENT LOOK**

(Contd. of page 8)

· **14.2 UN proper shipping name**  
 · **ADR** 1950 AEROSOLS  
 · **IMDG** AEROSOLS  
 · **IATA** AEROSOLS, flammable

· **14.3 Transport hazard class(es)**  
 · **ADR**



· **Class** 2.5F Gases.  
 · **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1 Gases.  
 · **Label** 2.1

· **14.4 Packing group**  
 · **ADR, IMDG, IATA** not regulated

· **14.5 Environmental hazards:** Not applicable.

· **14.6 Special precautions for user** Warning: Gases.  
 · **Hazard identification number (Kemler code):** -  
 · **EMS Number:** F-D,S-U  
 · **Stowage Code** SW1 Protected from sources of heat.  
 SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.  
 · **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:  
 Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.  
 For AEROSOLS with a capacity above 1 litre:  
 Segregation as for the appropriate subdivision of class 2.  
 For WASTE AEROSOLS:  
 Segregation as for the appropriate subdivision of class 2.

· **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.

· **Transport/Additional information:**

· **ADR**  
 · **Limited quantities (LQ)** 1L  
 · **Excepted quantities (EQ)** Code: E0  
 Not permitted as Excepted Quantity  
 · **Transport category** 2  
 · **Tunnel restriction code** D

· **IMDG**  
 · **Limited quantities (LQ)** 1L  
 · **Excepted quantities (EQ)** Code: E0  
 Not permitted as Excepted Quantity

(Contd. on page 10)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 27.09.2022

Version number 2 (replaces version 1)

Revision: 27.09.2022

**Trade name: DUPLI-COLOR CEMENT LOOK**

(Contd. of page 9)

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

### SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Directive 2012/18/EU

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.· **Seveso category P3a** FLAMMABLE AEROSOLS· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t· **LIST OF SUBSTANCES SUBJECT TO AUTHORISATION (UK ANNEX XIV)**· **Regulation (EC) No 273/2004 on drug precursors**

67-64-1	acetone	3
78-93-3	butanone	3

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

(Contd. on page 11)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 27.09.2022

Version number 2 (replaces version 1)

Revision: 27.09.2022

**Trade name: DUPLI-COLOR CEMENT LOOK**

(Contd. of page 10)

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**Carc. 2: Carcinogenicity – Category 2**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2**Asp. Tox. 1: Aspiration hazard – Category 1**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1**Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

GB