

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 11.01.2024

Version number 13 (replaces version 12)

Revision: 11.01.2024

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1 Product identifier

· **Trade name:** DC Alkyton various RAL-colours 150ml

· **Article number:** 269745, 269752, 269769, 269783, 269790, 269806, 269813

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

##### · **Sector of Use**

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Product category** PC9a Coatings and paints, thinners, paint removers

##### · **Process category**

PROC7 Industrial spraying

PROC11 Non industrial spraying

· **Application of the substance / the mixture** Lacquer

##### 1.3 Details of the supplier of the safety data sheet

##### · **Manufacturer/Supplier:**

European Aerosols GmbH\*

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@european-aerosols.com

\*Formerly known as Motip Dupli GmbH

· **Further information obtainable from:** Department Product Safety

##### 1.4 Emergency telephone number:

Tel.: +49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergency phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland:

Poison center if child has been poisoned: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

#### SECTION 2: Hazards identification

##### 2.1 Classification of the substance or mixture

· **Classification according to Regulation (EC) No 1272/2008**



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 11.01.2024

Version number 13 (replaces version 12)

Revision: 11.01.2024

**Trade name: DC Alkyton various RAL-colours 150ml**

(Contd. of page 1)

Eye Irrit. 2 H319 Causes serious eye irritation.  
 STOT SE 3 H336 May cause drowsiness or dizziness.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

#### Hazard pictograms



GHS02 GHS07

#### Signal word Danger

#### Hazard-determining components of labelling:

acetone

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (&lt;2%)

#### Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

#### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

#### Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### 2.3 Other hazards

#### Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

#### Dangerous components:

CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	12.5-<20%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas 1A, H220 Press. Gas (Comp.), H280	12.5-<20%

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31






Printing date 11.01.2024

Version number 13 (replaces version 12)

Revision: 11.01.2024

**Trade name: DC Alkyton various RAL-colours 150ml**

(Contd. of page 2)

EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (<2%)  Flam. Liq. 3, H226  Asp. Tox. 1, H304  STOT SE 3, H336 EUH066	12.5-<20%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8))  Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide  Carc. 2, H351	<2.5%

**Additional information:**

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.  
For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters -**
- **Protective equipment:** Mouth respiratory protective device.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.  
Keep away from ignition sources.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 11.01.2024

Version number 13 (replaces version 12)

Revision: 11.01.2024

Trade name: DC Alkyton various RAL-colours 150ml

See Section 13 for disposal information.

(Contd. of page 3)

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
  - Do not spray onto a naked flame or any incandescent material.
  - Keep ignition sources away - Do not smoke.
  - Keep respiratory protective device available.
  - Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
  - Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

#### · **Ingredients with limit values that require monitoring at the workplace:**

##### **67-64-1 acetone**

WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm  
Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

##### **106-97-8 butane (containing < 0,1 % butadiene (203-450-8))**

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm  
Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm  
Carc (if more than 0.1% of buta-1.3-diene)

##### **13463-67-7 titanium dioxide**

WEL Long-term value: 10\* 4\*\* mg/m<sup>3</sup>  
\*total inhalable \*\*respirable

#### · **DNELs**

##### **67-64-1 acetone**

Oral	DNEL	62 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	62 mg/kg /per day (Consumer, longterm systemic)
	DNEL	186 mg/kg /per day (Worker, longterm systemic)
Inhalative	DNEL	2420 mg/m <sup>3</sup> (Worker, acute local)
	DNEL	1210 mg/m <sup>3</sup> (Worker, longterm systemic)
	DNEL	200 mg/m <sup>3</sup> (Consumer, longterm systemic)
	DNEL	60 mg/m <sup>3</sup>

##### **Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (<2%)**

Oral	DNEL	125 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	208 mg/kg /per day (Worker, longterm systemic)
	DNEL	125 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	871 mg/m <sup>3</sup> (Worker, longterm systemic)
	DNEL	185 mg/m <sup>3</sup> (Consumer, longterm systemic)

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.01.2024

Version number 13 (replaces version 12)

Revision: 11.01.2024

**Trade name: DC Alkyton various RAL-colours 150ml**

(Contd. of page 4)

· **PNECs****67-64-1 acetone**

PNEC	10.6 mg/l (Freshwater)
PNEC	1.06 mg/l (Seawater)
PNEC	21 mg/l (Sporadic release)
PNEC	100 mg/l (Sewage treatment plant)
PNEC	30.4 mg/kg (Freshwater sediment)
PNEC	3.04 mg/kg (Seawater sediment)
PNEC	29.5 mg/kg (Soil)

· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**· **Appropriate engineering controls** No further data; see section 7.· **Individual protection measures, such as personal protective equipment**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· **Hand protection**

Protective gloves

· **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· **Eye/face protection**

Safety glasses



Tightly sealed goggles

GB

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 11.01.2024

Version number 13 (replaces version 12)

Revision: 11.01.2024

Trade name: DC Alkyton various RAL-colours 150ml

(Contd. of page 5)

### SECTION 9: Physical and chemical properties

#### · 9.1 Information on basic physical and chemical properties

##### · General Information

##### · Physical state

Aerosol

##### · Colour:

According to product specification

##### · Odour:

Characteristic

##### · Odour threshold:

Not determined.

##### · Melting point/freezing point:

Undetermined.

##### · Boiling point or initial boiling point and boiling range

-44.5 °C (-48.1 °F) (74-98-6 propane)

##### · Flammability

Not applicable.

##### · Lower and upper explosion limit

##### · Lower:

0.6 Vol % (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (&lt;2%))

##### · Upper:

13 Vol % (67-64-1 acetone)

##### · Flash point:

-97 °C (-142.6 °F) (74-98-6 propane)

##### · Auto-ignition temperature:

Not applicable, as aerosol.

##### · Decomposition temperature:

365 °C (689 °F)

##### · pH

Not determined.

##### · Viscosity:

Mixture is non-soluble (in water).

##### · Kinematic viscosity

Not determined.

##### · Dynamic:

Not determined.

##### · Solubility

##### · water:

Not miscible or difficult to mix.

##### · Partition coefficient n-octanol/water (log value)

Not determined.

##### · Vapour pressure at 20 °C (68 °F):

8300 hPa (6225.5 mm Hg) (74-98-6 propane)

##### · Vapour pressure at 50 °C (122 °F):

16500 hPa (12376 mm Hg)

##### · Density and/or relative density

##### · Density at 20 °C (68 °F):

0.7 g/cm<sup>3</sup> (5.8 lbs/gal)

##### · Relative density

Not determined.

##### · Vapour density

Not determined.

#### · 9.2 Other information

##### · Appearance:

##### · Form:

Aerosol

##### · Important information on protection of health and environment, and on safety.

##### · Explosive properties:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

##### · Solvent content:

##### · Organic solvents:

82.4 %

##### · VOC (EC)

---

577.1 g/l

##### · VOC-EU%

82.44 %

##### · Solids content:

17.1 %

##### · Change in condition

##### · Evaporation rate

Not applicable.

#### · Information with regard to physical hazard classes

##### · Explosives

Void

##### · Flammable gases

Void

##### · Aerosols

Extremely flammable aerosol. Pressurised container:  
May burst if heated.

##### · Oxidising gases

Void

##### · Gases under pressure

Void

##### · Flammable liquids

Void

##### · Flammable solids

Void

(Contd. on page 7)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 11.01.2024

Version number 13 (replaces version 12)

Revision: 11.01.2024

Trade name: DC Alkyton various RAL-colours 150ml

(Contd. of page 6)

· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

##### 67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	>15800 mg/kg (rabbit)
Inhalative	LC50 / 4h	76 mg/l (rat)
	LC50 / 96 h	5540 mg/l (oncorhynchus mykiss)

##### Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (<2%)

Oral	LD50	>5000 mg/kg /per day (rat) (OECD 401)
Dermal	LD50	>2000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4 h	>5000 mg/m3 (rat) (OECD 403)

- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

#### · Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

#### · 12.1 Toxicity

##### · Aquatic toxicity:

##### 67-64-1 acetone

LC50/96h	8300 mg/l (fish)
----------	------------------

(Contd. on page 8)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 11.01.2024

Version number 13 (replaces version 12)

Revision: 11.01.2024

**Trade name: DC Alkyton various RAL-colours 150ml**



(Contd. of page 7)

EC50/96h	7200 mg/l (algae)
LC50 / 48 h	8450 mg/l (crustacean (water flea))
<ul style="list-style-type: none"><li>· <b>12.2 Persistence and degradability</b> No further relevant information available.</li><li>· <b>12.3 Bioaccumulative potential</b> No further relevant information available.</li><li>· <b>12.4 Mobility in soil</b> No further relevant information available.</li><li>· <b>12.5 Results of PBT and vPvB assessment</b></li><li>· <b>PBT:</b> Not applicable.</li><li>· <b>vPvB:</b> Not applicable.</li><li>· <b>12.6 Endocrine disrupting properties</b> The product does not contain substances with endocrine disrupting properties.</li><li>· <b>12.7 Other adverse effects</b></li><li>· <b>Additional ecological information:</b></li><li>· <b>General notes:</b> Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.</li></ul>	

**SECTION 13: Disposal considerations**

· <b>13.1 Waste treatment methods</b>	
· <b>Recommendation</b>	Must not be disposed together with household garbage. Do not allow product to reach sewage system.
· <b>Uncleaned packaging:</b>	
· <b>Recommendation:</b>	Disposal must be made according to official regulations. Disposal must be made according to official regulations.

**SECTION 14: Transport information**

· <b>14.1 UN number or ID number</b>	
· <b>ADR, IMDG, IATA</b>	UN1950
· <b>14.2 UN proper shipping name</b>	
· <b>ADR</b>	1950 AEROSOLS
· <b>IMDG</b>	AEROSOLS
· <b>IATA</b>	AEROSOLS, flammable
· <b>14.3 Transport hazard class(es)</b>	
· <b>ADR</b>	
	
· <b>Class</b>	2 5F Gases.
· <b>Label</b>	2.1
· <b>IMDG, IATA</b>	
	
· <b>Class</b>	2.1 Gases.
· <b>Label</b>	2.1

(Contd. on page 9)



## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 11.01.2024

Version number 13 (replaces version 12)

Revision: 11.01.2024

**Trade name: DC Alkyton various RAL-colours 150ml**

(Contd. of page 8)

· <b>14.4 Packing group</b> · <b>ADR, IMDG, IATA</b>	not regulated
· <b>14.5 Environmental hazards:</b>	Not applicable.
· <b>14.6 Special precautions for user</b> · <b>Hazard identification number (Kemler code):</b> · <b>EMS Number:</b> · <b>Stowage Code</b>	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· <b>Segregation Code</b>	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	1L Code: E0 Not permitted as Excepted Quantity
· <b>Transport category</b> · <b>Tunnel restriction code</b>	2 D
· <b>IMDG</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	1L Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1

## SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Directive 2012/18/EU
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.

(Contd. on page 10)

GB

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 11.01.2024

Version number 13 (replaces version 12)

Revision: 11.01.2024

**Trade name: DC Alkyton various RAL-colours 150ml**

(Contd. of page 9)

H226 *Flammable liquid and vapour.*  
 H280 *Contains gas under pressure; may explode if heated.*  
 H304 *May be fatal if swallowed and enters airways.*  
 H319 *Causes serious eye irritation.*  
 H336 *May cause drowsiness or dizziness.*  
 H351 *Suspected of causing cancer.*  
 EUH066 *Repeated exposure may cause skin dryness or cracking.*

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
 ICAO: International Civil Aviation Organisation  
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 VOC: Volatile Organic Compounds (USA, EU)  
 DNEL: Derived No-Effect Level (UK REACH)  
 PNEC: Predicted No-Effect Concentration (UK REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Gas 1A: Flammable gases – Category 1A  
 Aerosol 1: Aerosols – Category 1  
 Press. Gas (Comp.): Gases under pressure – Compressed gas  
 Flam. Liq. 2: Flammable liquids – Category 2  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 Carc. 2: Carcinogenicity – Category 2  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
 Asp. Tox. 1: Aspiration hazard – Category 1

· **\* Data compared to the previous version altered.**

GB