

DUPLI-COLOR AUTO COLOR SPRAY 2-COAT CLEAR LACQUER

Ord.-no.: 535307, 711084



Technical Information

Weather-resistant, high gloss finish for DUPLI-COLOR acrylic sprays. Absolutely necessary to seal all metallic and pearl lacquers to protect them from weathering and environmental impact.

Quality & properties

- High-grade acrylic quality
- Suitable for indoors and outdoors applications
- Polishable
- Weather-resistant, light-proof, UV-proof (non-yellowing)
- Scratch-, shock- and impact-resistant
- Quick-drying
- Durable gloss
- Excellent adhesion
- Very hard surface, good elasticity
- Limited resistance against petrol

Physical & chemical data

- Base: Acrylate copolymers
- Colourname: transparent
- Smell: Characteristic
- Degree of gloss: gloss, >75 GU
- Efficiency:
 - ◊ 400 ML – 1.3 m²
 - ◊ 150 ML – 0.5 m²
- Dry to touch: 50 min
- Dust dry: 10 min
- Completely dry: 24 h
- Overcoatable: 30 min
- Surfaces: Suitable for indoors and outdoors applications
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 4000/20 bar
- Flash point: n.a.
- Storage stability: 10 y
- Content:
 - ◊ 400 ML
 - ◊ 150 ML

How to use

- Let the DUPLI-COLOR Metallic coat dry for at least 30 minutes.
- Before use, shake the clear lacquer can for 1 minute.
- Spray from a distance of 25 cm several thin cross-coats of the clear lacquer.
- Do not spray over surfaces which are painted with synthetic resin lacquer!
- After 24 hours drying time the spray dust can be polished off with presto Polishing Paste.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of September 18, 2023 – This release replaces all eventually earlier issued versions.

