

DUPLI-COLOR RUST STOP EPOXY PRIMER

Ord.-no.: 103635

Technical Information



RUST STOP EPOXY PRIMER is an all-purpose 1K primer that provides excellent adhesion and corrosion prevention on sheet steel, zinc-coated steel, aluminium and anodised aluminium. It is fast drying with good flow and can be applied wet-on-wet. It also offers good insulation against humidity. It is best to pre-clean metal surfaces thoroughly with DUPLI-COLOR silicone remover (art. no. 375439), for fibreglass surfaces use DUPLI-COLOR plastic cleaner (art. no. 373077).

Quality & properties

- Excellent adhesion and corrosion protection for steel, galvanized steel, aluminium and fibreglass
- Simple, time-saving application
- Fast drying
- Good flow
- Recoat with DUPLI-COLOR RUST STOP paints
- Good insulation against moisture
- Wet-on-wet application possible

Physical & chemical data

- Base: 1K Epoxy resin
- Colourname: grey
- Smell: Characteristic
- Degree of gloss: mat, 10 ± 2 GU
- Efficiency: 400 ML – 1 m²
- Dust dry: 5 min
- Dry to touch: 15 min
- Completely dry: 30 min
- Overcoatable: 12-15 min
- Surfaces: Blank metal sanded, zinc coated cleaned and sanded, aluminium, enodized aluminium, old paints cleaned and sanded, glass fiber materials cleaned and sanded, plastic substrates first priming with DUPLI-COLOR Plastic Primer
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 4000/20 bar
- Temperature Resistance: grey 90 °C
- Storage stability: 10 y
- Content: 400 ML

How to use

- Remove all rust from metal surfaces
- Clean surface with DUPLI-COLOR Silicone Remover and sand
- Clean glassfibre surface with Plastic Cleaner
- Shake the can well for 3 minutes
- Carry out test spray
- Spray distance: approx. 25 cm
- Spray in several thin layers

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 12, 2024 – This release replaces all eventually earlier issued versions.

