

# DUPLI-COLOR GLITTER SPRAY

Ord.-no.: look at ordering information

## Technical Information



Special glitter painting for all kinds of surfaces e.g. glass, ceramics, stone, metals and all surfaces, which are painted with acrylic or nitro-combi lacquers. Also for wood (primed or painted); limited suitable on carton, paper and coatable plastics. With silver glitter particles to be applied on colored surfaces. Colored fulltones for covering paintings. The effect you achieve depends strongly from color and quality of the surface.

### Quality & properties

- High-grade nitro-combi quality
- Excellent adhesion
- Good flow, smooth surface
- Resistant to wiping
- Suitable for lacquering indoors and outdoors objects
- Resistant to wiping
- Weather-resistant, light-proof, UV-resistant
- Scratch-, shock- and impact-resistant

### Physical & chemical data

- Base: Nitrocombi resin
- Colourname:
  - ◊ silver transparent
  - ◊ blue black
  - ◊ gold
  - ◊ copper brown
  - ◊ lime green
  - ◊ marin blue
  - ◊ purple
  - ◊ violet
- Smell: Characteristic
- Efficiency:
  - ◊ 400 ML – 1.0 - 1.5 m<sup>2</sup>
  - ◊ 200 ML – 0.5 - 0.7 m<sup>2</sup>
  - ◊ 150 ML – 0.4 - 0.6 m<sup>2</sup>
  - ◊ 200 ML – 0,5 - 0,7 m<sup>2</sup>
- Dust dry: 10 min
- Dry to touch: 60 min
- Completely dry: 24 h
- Overcoatable: 10 min
- Surfaces: glass, ceramics, stone, metals and all surfaces, which acrylic or nitro-combi lacquers, wood, limited suitable on carton, paper and coatable plastics
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 8300/20 bar
- Storage stability: 10 y
- Content:
  - ◊ 400 ML
  - ◊ 200 ML
  - ◊ 150 ML

### How to use

- Remove flakes of old paint and rust.
- The ground has to be clean, dry and free from fat.
- Mask off areas not to be painted.
- If necessary prime DUPLI-COLOR Primer. To achieve a covering layer of the effect, prime first Diamond Effect Gold with white Effect Primer and the other covering colours with black Effect Primer
- Before use, shake can for 3 minutes.
- Test spray at an invisible spot.
- Spray in 2 minute intervals several thin coats from a distance of approx. 25 cm.
- Do not spray over surfaces which are painted with synthetic resin lacquer!
- The Diamond-effect strongly depends from colour of the ground. The silver-transparent product is best on

painted or coloured objects. The same effect you achieve with the covering products marine, gold or blue-black on not-painted objects.

- For durable resistance we recommend to apply a protective coat of DUPLI-COLOR Zapon Spray.

#### **Environmentally friendly**

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### **Disposal**

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

#### **Marking/Labeling**

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of December 5, 2024** – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)  
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)