

## DUPLI-COLOR NEXT CLEAR COAT

## Technical Information



Innovative spraypaint for easy application and high reliability for a perfect spray result: Can be applied on synthetic lacquers (alkyd lacquers) as well as on acrylic lacquers! The neutral smell allows to spray outside and let it dry inside. Very convenient spray paint due to easy application, very good coverage and adhesion. For many possibilities in decoration, DIY, handicraft and even for artists.

**Ord.-no:** 480416, 480812

### Quality & properties

- Neutral smell
- Easy application while universal compatibility with other paints (acrylic or alkyd quality, earliest after 1 week drying time of the alkyd painting)
- Perfect adhesion on many surfaces without a primer.
- Even for direkt paintings on styrofoam or paintable hard plastics
- Soft spraying with very good flow
- Fast-drying
- Excellent coverage
- Suitable for indoor and outdoor use
- Flexible top-coat
- Scratch-resistant
- Solvents used are biodegradable

### Physical & chemical data

- Base: Polyester resin
- Colourname: transparent
- Degree of gloss:
  - gloss GU
  - satin mat GU
- Efficiency: 400 ML – 2 m<sup>2</sup>
- Dust dry: 10-20 min
- Completely dry: 24 h
- Overcoatable: 2 h
- Surfaces: Glas;Plastic;Styrofoam;Stone;Wood; Metal;Textiles;Universal
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content: 400 ML

### How to use

The surface must be clean, absolutely fat-free and dry. Remove loose parts.  
 In spite of low formation of spray mist, we recommend to protect the surrounding area.  
 Alkyd paintings should be overpainted with NEXT earliest after 1 week drying time.  
 Shake can for 3 minutes, test spray.  
 The optimal distance is approx. 25 cm.  
 Spray in 2 - 4 minute intervals several thin layers. Shake can, before you apply the next layer.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 13, 2025** – This release replaces all eventually earlier issued versions.