

DUPLI-COLOR ALL SEASON

Technical Information



High-covering, scratch- and weather-resistant quality lacquer makes everyday things shine in a new gloss. For even and smooth surfaces – indoors and outdoors. High-grade synthetic lacquer in high gloss, matt and satin matt RAL and fashion colours. Suitable for wood, metal, glass, stone or coatable hard plastics.

Ord.-no: 254529, 466861, 466878, 466885, 466960, 467042, 668876, 668883, 674044, 440755, 466540, 466571, 466625, 466663, 466694, 466724, 466762, 466809, 466830, 466854, 466908, 466922, 466953, 467004, 467011, 467035, 467059, 467066, 467080, 467561, 467592, 470981, 471001, 748882, 884795, 884801, 884818, 162923, 470998, 592836, 430343, 466649, 466700, 466984, 470974, 476051, 506031, 623394, 884733, 884788, 748790

Quality & properties

- High-grade synthetic quality
- Fast-drying
- Suitable for indoors and outdoors applications
- Good coverage and filling power
- Good colour and gloss retention
- Resistant to weathering, light-proof, UV-resistant
- Excellent flow for even surfaces
- Good adhesion on nearly all surfaces
- Scratch-, bump- and impact-proof

Physical & chemical data

Base: Alkyd resin

Colourname:

- sapphire blue
- silver grey
- light grey
- nut brown
- cream
- leaf green
- ultramarine blue
- signal white
- iron grey
- daffodil yellow
- ivory
- colza yellow
- pastel orange
- flame red
- gentian blue
- light blue
- yellow green
- chocolate brown
- pure white
- reseda green
- deep black
- ruby red
- traffic purple
- pastel yellow
- vermilion
- moss green
- heather violet
- zinc yellow
- blue lilac
- light rose
- pastel blue
- carmine red
- mint green
- traffic white
- melon yellow
- light ivory

Degree of gloss:

- mat GU
- gloss GU

Efficiency:

- 400 ML – 1.0 - 1.4 m²
- 400 ML – 1.0 - 1.4 m²

Dry to touch:

- 4 h
- 4 min

Dust dry: 30 min

Completely dry: 24 h
Overcoatable: 2 + 24 h
Surfaces: wood, metal, glass, stone or coatable
hard plastics
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Flash point: n.a.
Storage stability: 10 y
Content: 400 ML

How to use

The ground has to be clean, dry and fat-free
Remove loose flakes of old paints and de-rust, then sand and prime.
Before painting plastic parts, use DUPLI-COLOR Plastic Primer.
Let dry for 1 - 2 hours.
Mask off surfaces not to be painted.
Before use, shake can for 3 minutes.
Test colour of spray and compatibility at an invisible spot.
Spray distance: approx. 25 cm
Spray several thin coats in approx. 2 minute intervals.
Re-coatable within 2 hours or not earlier than after 24 hours.
Do not coat with acrylic lacquer - not even after curing!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.