

## DUPLI-COLOR TERRACOTTA LOOK

## Technical Information



Quick-drying special lacquer with strikingly similar surface structure. Terracotta style for chairs, benches, shelves, bowls etc. For all kinds of surfaces. Suitable for inside and outside use.

**Ord.-no:** 706981, 743658, 743665, 743634, 743641

### Quality & properties

High-grade nitro-combi quality with special, rough texture  
Excellent adhesion and coverage  
Good flow  
Quick-drying  
Suitable for painting and repair of indoors and outdoors objects  
Weather-resistant  
Excellent colour retention: (light-proof, UV-resistant)  
Excellently re-coatable

### Physical & chemical data

Base: Nitrocombi resin  
Colourname:  

- manganese brown
- velvet blue
- orient red
- sehara yellow

Degree of gloss: mat GU  
Efficiency:  

- 400 ML – 0.8 - 1.2 m<sup>2</sup>
- 150 ML – 0.3 - 0.5 m<sup>2</sup>

Dry to touch: 50 min  
Dust dry: 10 min  
Completely dry: 3 h  
Surfaces: metal, wood, glass, stone, ceramics, carton and many coatable hard plastics  
Minimum Working Temperature: 10 °C  
Maximum Working Temperature: 25 °C  
Flash point: n.a.  
Storage stability: 10 y  
Content:  

- 400 ML
- 150 ML

### How to use

Clean underground from dirt and fat. Derust metals.

On plastic parts always use DUPLI-COLOR Plastic Primer; on other surfaces use DUPLI-COLOR Primer or Universal Primer.

Fill and sand uneven surfaces. Let dry.

The surface has to be clean, dry and free from fat.

Mask off areas not to be painted.

Before use, shake the can vigorously for 3 minutes.

Spray several thin coats in 3 - 5 minute intervals.

Spray from a distance of approx. 25 cm.

Terracotta Effect can be re-coated with any DUPLI-COLOR spray paint. Depending on thickness of the applied coat, the intensity of the achieved structure can degrease.

Do not spray over synthetic paints!

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.