

## DUPLI-COLOR TUNING METALLIC

## Technical Information



Quick-drying acrylic lacquers for styling, contrast lacquering and repairs on the vehicle.

**Ord.-no:** 133886, 191893, 191923, 133961, 191930, 133923, 191916

### Quality & properties

- High-grade acrylic nitrocombi quality
- Very good coverage
- Excellent adhesion
- Very good colour retention (light-proof, non-yellowing)
- After coating with clear lacquer weather-resistant and polishable.
- Durable gloss
- Quick-drying
- Good flow, smooth surface
- Limited resistance to petrol
- Scratch-, shock- and impact-resistant

### Physical & chemical data

- Base: Acrylic resin
- Colourname:
  - blue
  - red
  - silver
  - violett
  - violet
- Degree of gloss: satin mat GU
- Efficiency:
  - 150 ML – 0.5 m<sup>2</sup>
  - 400 ML – 1.3 m<sup>2</sup>
- Dry to touch: 30 min
- Dust dry: 10 min
- Completely dry:
  - 24 h
  - 24 min
- Overcoatable: 30 min
- Surfaces: metals, glass, ceramics, stone and many other surfaces
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content:
  - 150 ML
  - 400 ML

### How to use

Clean underground from dirt, fat and rust.

Treat existing pore rust with presto Deruster.

Fill and sand uneven surfaces. If there is no putty necessary, apply DUPLI-COLOR Primer. Otherwise apply DUPLI-COLOR Filler Spray on the fine-sanded putty layer.

Generously mask off the repair spot. Larger surfaces should be masked off at creases and edges of the car body, too.

Smooth the thoroughly dried Filler layer by wet-sanding (sandpaper P1000).

Before use, shake the can vigorously for 3 minutes.

The spray distance should be approx. 20-30 cm.

Spray the metallic lacquer in 3 - 5 minute intervals several thin coats onto the dry repair spot.

Metallic paints have to be sealed after 30 minutes drying time with clear lacquer. Otherwise the aluminium parts in the lacquer will be attacked by environmental and weathering influences.

Do not spray over synthetic paints!

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.