

DUPLI-COLOR DISPERSION REPAIR PAINT

Technical Information



Dispersion repair paint for dirty subsurfaces such as walls or ceilings. Applicable for spots caused by grease, nicotine, soot and water as well as stain of insects, coffee, bitumen, tar and crayons.

Well suitable for use on subsurfaces such as polystyrene, wallpaper, old wall paint and plaster.

Ord.-no: 391408

Quality & properties

- High covering power
- Odourless
- Water-based
- Very good efficiency (up to 1 m² / spray can)
- Excellent insulating effect
- Usage indoor and outdoor
- Recoatable with dispersion colours
- Shade of white mat

Physical & chemical data

- Base: acrylate dispersion
- Colourname: white
- Smell: Neutral
- Efficiency: 200 ML – 1 m²
- Dust dry: 30 min
- Dry to touch: 40 min
- Overcoatable: 2 h
- Surfaces: polystyrene, wallpaper, old wall paint, ceilings and plaster
- Minimum Working Temperature: +10 °C
- Maximum Working Temperature: +25 °C
- Storage stability: 2 years
- Content: 200 ML

How to use

- Before use, shake the can for 2 minutes.
- The surface has to be clean and dry.
- Drily brush water streaks, remove salt efflorescences.
- Initially test spray.
- Apply from a distance of approx. 25 cm several thin cross-coats.
- To increase the insulating effect, let surfaces dry.
- For difficult spots, repeat application if necessary.
- Recoatable with dispersion colours.
- Protect from frost.
- After application clean the sprayhead in order to make a further use of the spray can possible.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of July 10, 2025 – This release replaces all eventually earlier issued versions.