

DUPLI-COLOR Magnetic Blackboard Paint Click & Write

Technical Information



Click & Write Magnetic Blackboard Paint is a ferro-magnetic blackboard paint. After application you can write on the painted surface with common chalk and simply wash it off with water. Besides, the ferrous components allow to adhere magnets. The product can be used on various grounds, e.g. metal, wood, stone and different plastics.

Ord.-no: 447174

Quality & properties

- High-grade special lacquer on alkyd resin basis
- Allows to affix magnets
- To write and draw on with chalk
- Very good adhesion on the ground
- Scratch- and shock-proof
- Resistant to cleansing agents
- Very good coverage
- Colour: black matt

Physical & chemical data

- Base: Alkyd resin
- Colourname: black
- Degree of gloss: mat GU
- Efficiency: 500 ML – 1,8 - 2,0 m²
- Dry to touch: 2 - 3 h
- Dust dry: 30 - 60 min
- Completely dry: 48 h
- Surfaces: metal, wood, stone and different plastics
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content: 500 ML

How to use

- The surface to be treated should be clean, dry and fatfree.
- Remove and sand down layers of old painting till the surface is totally even.
- If necessary (on absorbant surfaces), prime with DUPLI-COLOR Primer.
- Before use shake the can for 2 minutes and spray a test piece.
- Optimal spray distance: 15 - 20 cm.
- To get the optimal magnetic effect on the blackboard, you should apply at least 5 layers; let dry each layer for 10 minutes before you apply the next one.
- Shake the can from time to time during use.
- After use turn the can upside down and spray the valve empty to clean it.
- After 48 hours the lacquer is hardened and can be used as blackboard.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 21, 2025 – This release replaces all eventually earlier issued versions.