

DUPLI-COLOR LINEMARKER

Technical Information



Special Marking Spray for long-term markings. Extremely durable. Suitable for markings on car parks, parking lots, industrial applications and marking lines for private purposes. With upside-down-valve. Optional accessory: Marking Trolley.

Ord.-no: 895142, 895159, 895166, 895173, 895142-KD, 895159-KD, 895166-KD, 895173-KD

Quality & properties

High coverage, quick drying quality
Special valve for floor applications ensures sharp edges
Specially for use in Speedliner²
For permanent markings
Highly resistant to abrasion
High weather resistance

Physical & chemical data

Base: Acrylic resin
Colourname:

- blue
- yellow
- red
- white

Efficiency: 600 ML – 60 m
Dry to touch: 30 min
Dust dry: 10 min
Completely dry: 24 h
Overcoatable: 24 h
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Flash point: n.a.
Content: 600 ML

How to use

Shake can for approx. 3 minutes. After you hear the sound of the balls inside the can, vigorously shake the can for one more minute.
Test spray at an invisible spot.
Spray distance approx. 25 cm.
Apply the desired marking.
In case of use in the Speedliner² marking trolley, attend to the corresponding manual.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of June 13, 2025 – This release replaces all eventually earlier issued versions.