

DUPLI-COLOR ELOXAL SPRAY

Technical Information



A quick-drying special lacquer with excellent hiding power and extremely good weather resistance.

For color-matching painting and repair of surface scratches and damages on eloxated surfaces as doors, windows, shower cabins, hi-fi-devices etc.

Ord.-no: 299780, 299797, 299803, 299810, 323003, 299780-AT, 299780-AW, 299780-DW, 299797-AT, 299797-AW, 299797-DG, 299797-DW, 299803-AW, 299803-DG, 299810-AT, 299810-AW, 299810-DG, 299810-DW, 323003-AT, 323003-AW, 323003-DW

Quality & properties

High-grade nitro-combi quality
Matching to eloxated aluminium
Very good coverage
Excellent adhesion
Good flow, smooth surface
Quick-drying
Suitable for indoors and outdoors applications
Weather-resistant, light-proof, UV-resistant
Scratch-, shock- and impact-resistant

Physical & chemical data

Base: Nitrocombi resin
Colourname:

- dark bronze
- medium bronze
- bronze
- silver
- dark gold

Smell: Characteristic
Degree of gloss value: semi mat, 25 ±5
Efficiency: 400 ML – 0.8 - 1.0 m²
Dust dry: 15 min
Dry to touch: 30 min
Completely dry: 24 h
Surfaces: doors, window frames, shower cubicles, hi-fi equipment etc.
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Flash point: n.a.
Storage stability: 10 years
Content: 400 ML

How to use

The surface has to be clean, dry and free from fat.
If necessary, apply DUPLI-COLOR METAL PRIMER or UNIVERSAL PRIMER.
Cover areas not to be painted.
Before use, shake the can for 2-3 minutes.
Test spray to check colour-matching and compatibility.
Spray several thin coats.
Spray from a distance of approx. 25 cm
Best results will be achieved during temperatures around 20°C.
Do not apply on synthetic paints!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of July 10, 2025 – This release replaces all eventually earlier issued versions.