

DUPLI-COLOR UNIVERSAL PRIMER

Technical Information



This Primer for universal use grants the excellent adhesion of the subsequent top coating with DUPLI-COLOR synthetic, nitro-combi or acrylic spray paints. Suitable for the most surfaces, such as ceramics, eternite, carton, of course even on wood and metal.

Ord.-no: 325021, 328046, 467486, 319648, 319648-DF, 325021-AT, 325021-DG, 325021-DW, 328046-DG, 467486-AT, 467486-DG, 467486-DW

Quality & properties

- High-grade nitro-combi quality
- Especially high filling power
- Very good flow, smooth surface
- Quick-drying
- Protects from corrosion
- Promotes best adhesion of the top coat on the subsoil
- Optimizes the gloss of the top coat
- Grants the economical application of the top coat
- For indoor and outdoor applications

Physical & chemical data

- Base: Nitrocombi resin
- Colourname:
 - grey
 - red
 - beige
- Smell: Characteristic
- Degree of gloss value: mat, 10 ±2
- Efficiency: 400 ML – 0.8 m²
- Dust dry: 15 min
- Dry to touch: 30 min
- Overcoatable: 2 - 4 h
- Surfaces:
 - Ceramics, eternite, carton, wood and metal.
 - Ceramics, eternite, carton, wood and metal
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Storage stability: 10 years
- Content:
 - 400 ML
 - 150 ML

How to use

De-rust, sand and clean the surfaces to be painted.
Apply putty, if necessary.
The surface has to be clean, dry and free from rust and fat.
Shake cans for 2 minutes.
Test colour of spray and compatibility at an invisible spot.
Egalize little dents and porous repair spots by repeated spraying of thin layers and sanding.
Spray from a distance of approx. 25 cm.
After drying (approx. 2-4 hours), wet-sand with sandpaper (grain 600), clean the surface and let it dry.
Afterwards apply the top coat.
Coatable with synthetic, nitro-combi or acrylic lacquers.
Do not spray over synthetic lacquers!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of July 10, 2025 – This release replaces all eventually earlier issued versions.