

## DUPLI-COLOR UNIVERSAL PRIMER

## Technical Information



This Primer for universal use grants the excellent adhesion of the subsequent top coating with DUPLI-COLOR synthetic, nitro-combi or acrylic spray paints. Suitable for the most surfaces, such as ceramics, eternite, carton, of course even on wood and metal.

**Ord.-no:** 325021, 328046, 467486, 319648, 319648-DF, 325021-AT, 325021-DG, 325021-DW, 328046-DG, 467486-AT, 467486-DG, 467486-DW

### Quality & properties

- High-grade nitro-combi quality
- Especially high filling power
- Very good flow, smooth surface
- Quick-drying
- Protects from corrosion
- Promotes best adhesion of the top coat on the subsoil
- Optimizes the gloss of the top coat
- Grants the economical application of the top coat
- For indoor and outdoor applications

### Physical & chemical data

- Base: Nitrocombi resin
- Colourname:
  - grey
  - red
  - beige
- Degree of gloss: mat GU
- Efficiency: 400 ML – 0.8 m<sup>2</sup>
- Dry to touch: 30 min
- Dust dry: 15 min
- Overcoatable: 2 - 4 h
- Surfaces:
  - Ceramics, eternite, carton, wood and metal.
  - Ceramics, eternite, carton, wood and metal
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content:
  - 400 ML
  - 150 ML

**How to use**

De-rust, sand and clean the surfaces to be painted.  
Apply putty, if necessary.  
The surface has to be clean, dry and free from rust and fat.  
Shake cans for 2 minutes.  
Test colour of spray and compatibility at an invisible spot.  
Egalize little dents and porous repair spots by repeated spraying of thin layers and sanding.  
Spray from a distance of approx. 25 cm.  
After drying (approx. 2-4 hours), wet-sand with sandpaper (grain 600), clean the surface and let it dry.  
Afterwards apply the top coat.  
Coatable with synthetic, nitro-combi or acrylic lacquers.  
Do not spray over synthetic lacquers!

**Environmentally sound**

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal**

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling**

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.