

DUPLI-COLOR ISOLATING PRIMER

Technical Information



Isolating primer for painting and reconditioning work in the interior and external area. Prevents the come through at problem places such as edges of water, fat -, soot and nicotine marks, oily or aqueous materials before over-painting with top coats.

Also excellently suitable as primer for all sucking undergrounds, Underground before changing wallpapers, as protection layer for outside on concrete, plaster and walls against strong weather influences, like strong rain etc.

Ord.-no: 657092

Quality & properties

- Special binder on polyvinyle resin basis
- Very good coverage
- Good flow, smooth surface
- Quick-drying
- Very good resistance against environmental influences
- Resistant to yellowing
- Can be coated with all current lacquers and dispersions

Physical & chemical data

- Base: Special resin
- Colourname: white
- Degree of gloss: mat
- Efficiency: 400 ML – 1.0 - 2.0 m²
- Overcoatable: 15 min
- Surfaces: painting and reconditioning work in the interior and external area
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content: 400 ML

How to use

- Remove tough dirt and loose parts.
- The ground has to be dry.
- Before use, shake can for 3 minutes.
- Spray from a distance of approx. 25 cm several thin coats.
- Can be coated with all current lacquers and dispersions.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.