

DUPLI-COLOR Flip Flop / Flip Flop Ultra Automotive

Technical Information



Color change effect for individually creations. Depending on incidence of light and perspective of the spectator, the effect changes the colour. Specially impressing effect is achieved on a dark ground. Suitable for glass, ceramics, stone, metals, etc.

Ord.-no: 665509, 665516, 164637, 173899, 164620, 164996

Quality & properties

High-grade nitro-combi quality with a combination of special binders and pigments
 Good flow, smooth surface
 Quick-drying
 Weather-resistant, light-proof, UV-resistant
 Scratch-, shock- and impact-resistant
 Very efficient
 High degree of gloss
 Round spray jet, fine atomization
 Very smooth, level run
 Vampire: violet to green
 scarab: green to anthracite
 tropical: red to gold/brown
 ultra lagoon: violet to bordeaux red
 ultra lapis: azure blue to turquoise
 ultra sunrise: green brown to gold
 ultra miracle: silver chromaflair

Physical & chemical data

Base: Nitrocombi resin
 Colourname:
 ◦ green/violet
 ◦ light red/dark red
 ◦ light blue/dark blue
 ◦ light green/dark green
 ◦ light violet/dark violet
 ◦ multicolor/silver
 Smell: Characteristic
 Degree of gloss value: gloss, 75
 Efficiency: 150 ML – 0.4 m²
 Dust dry: 5 min
 Dry to touch: 30 min
 Completely dry: 24 h
 Overcoatable: 1 h
 Surfaces: glass, ceramics, stone and metals
 Minimum Working Temperature: 10 °C
 Maximum Working Temperature: 25 °C
 Flash point: n.a.
 Storage stability: 10 years
 Content: 150 ML

How to use

The ground has to be clean, dry and free from fat.
Mask off areas not to be painted.
Before use, shake can for 3 minutes.
Test spray at an invisible spot.
Spray several thin coats from a distance of approx. 25 cm.
Let lift off for 5 minutes after every cross coat.
The effect as shown on the cap will be achieved with 3 - 4 cross coats.
To increase the gloss and weather-resistance, we recommend to apply a top coat of acrylic clear lacquer.
Do not spray over surfaces which are painted with synthetic resin lacquer!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of July 10, 2025 – This release replaces all eventually earlier issued versions.