

## DUPLI-COLOR MODEL PAINT PLASTIC PRIMER

## Technical Information



Special primer for model making. To prime models like airplanes, cars, ships and boat models before applying a top coat of synthetic, acrylic or nitro combi lacquer.

Ord.-no: 685255

### Quality & properties

Solvent-based product with special adhesion-promoting additives  
For the subsequent painting of coatable hard plastics  
Quick-drying  
Suitable for indoors and outdoors applications  
Good resistance to outside influences  
Good flow, smooth surface

### Physical & chemical data

Base: Special resin  
Colourname: transparent  
Efficiency: 150 ML – 2 - 2,5 m<sup>2</sup>  
Dust dry: 5 min  
Completely dry: 15 min  
Overcoatable: 15 min  
Surfaces: model painting  
Minimum Working Temperature: 10 °C  
Maximum Working Temperature: 25 °C  
Flash point: n.a.  
Storage stability: 10 y  
Content: 150 ML

### How to use

Clean surface from dirt, fat and silicone.  
Evtl. sand with sandpaper grain 600.  
Remove abrasive dust.  
Before use, shake can for 3 minutes.  
Apply max. 2 thin layers.  
Spray from a distance of approx. 25 cm.  
After drying (approx. 15 minutes) coatable with acrylic, synthetic or nitro-combi lacquers.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 21, 2025** – This release replaces all eventually earlier issued versions.