

## DUPLI-COLOR AQUA LACK Clear Coat

## Technical Information



For environment-conscious spraying in a quick-drying, waterbased acrylic quality. With a good coverage. You determine the colour depth from translucent to opaque. Weather-resistant after curing, suited for polystyrene. A special spray technology reduced spraydust. Vanilla smell instead of annoying solvent odour - 90 % of the solvents were replaced by water. These properties allow to spray even in interior rooms. Acc. to DIN EN 71-3 suitable for the painting of toys.

**Ord.-no:** 476389

### Quality & properties

High-quality acrylic lacquer, waterbased  
Less spray mist, therefore pleasant usage even indoor  
Suitable for polystyrene  
Eco friendly  
Waterbased  
Suitable for toys

### Physical & chemical data

Base: Waterbased acrylic resin  
Colourname: transparent  
Smell: Vanilla  
Degree of gloss value: semi mat, 25 ±5  
Efficiency: 150 ML – 1.0 - 2.0 m<sup>2</sup>  
Dust dry: 15 - 20 min  
Dry to touch: 2 h  
Completely dry: 24 h  
Surfaces: wickerware, wood, carton, metal, fabric, paintable hardplastics, glass, ceramics, polystyrene  
Minimum Working Temperature: +10 °C  
Maximum Working Temperature: +25 °C  
Flash point: n.a.  
Storage stability: 4 years  
Content: 150 ML

### How to use

The surface must be clean, absolutely fat-free and dry. Remove loose parts. In spite of low formation of spray mist, we recommend to protect the surrounding area. Pre-paint absorbent grounds with AQUA Primer. Let dry (at least 2 hours). Prime hardplastics with a Plastic Primer. Shake can for 3 minutes, test spray. The optimal distance is approx. 25 cm. Spray in 2 minute intervals several thin layers. AQUA spray paint should not be applied during temperatures lower than 15°C, as this might delay drying time.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of July 10, 2025** – This release replaces all eventually earlier issued versions.