

DUPLI-COLOR AQUA LACK

Technical Information



For environment-conscious spraying in a quick-drying, waterbased acrylic quality. With a good coverage. You determine the colour depth from translucent to opaque. Weather-resistant after curing, suited for polystyrene. A special spray technology reduced spraydust. Vanilla smell instead of annoying solvent odour - 90 % of the solvents were replaced by water. These properties allow to spray even in interior rooms. Acc. to DIN EN 71-3 suitable for the painting of toys.

Ord.-no: 246258, 246265, 246272, 246289, 246296, 246302, 246319, 252440, 252457, 252471, 252488, 252501, 252518, 252525, 252532, 373862, 373879, 373978, 373787, 373794, 373800, 373817, 373824, 373831, 373848, 373855, 373886, 373893, 373909, 373916, 373923, 373930, 373961, 476402, 476419, 476426, 476433, 476440, 476457, 476464, 476471, 476488, 476495, 476501, 476518, 476525, 476532, 476563, 476570, 476594, 476600

Quality & properties

High-quality acrylic lacquer, waterbased
Less spray mist, therefore pleasant usage even indoor
Suitable for polystyrene
Eco friendly
Waterbased
Suitable for toys

Physical & chemical data

Base: Waterbased acrylic resin

Colourname:

- traffic yellow
- pastel orange
- telemagenta
- anthracite grey
- ice blue
- spring green
- terracotta
- colza yellow
- vermillion
- gentian blue
- light blue
- yellow green
- silver grey
- chocolate brown
- creme white
- beige
- black brown
- mole brown
- mittelgelb
- orange
- scharlachrot
- carmine red
- rosa
- ultramarine blue
- light turquoise
- may green
- grey
- dark grey
- anthracite
- white
- broken white
- black
- pistachio green
- deep black
- flame red
- silver
- gold

Smell: Vanilla

Degree of gloss value:

- gloss, 75
- semi mat, 25 ±5

Efficiency: 350 ML – 0.8 - 1.2 m²

Dust dry:

- 20 min
- 15 - 20 min

Dry to touch: 2 h

Completely dry: 24 h
Overcoatable: 24 h
Surfaces: wickerware, wood, carton, metal, fabric,
paintable hardplastics, glass, ceramics, polystyrene
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Flash point: n.a.
Storage stability: 4 years
Content:

- 350 ML
- 150 ML

How to use

The surface must be clean, absolutely fat-free and dry. Remove loose parts. In spite of low formation of spray mist, we recommend to protect the surrounding area. Pre-paint absorbent grounds with AQUA Primer. Let dry (at least 2 hours). Prime hardplastics with a Plastic Primer.

Shake can for 3 minutes, test spray. The optimal distance is approx. 25 cm. Spray in 2 minute intervals several thin layers. AQUA spray paint should not be applied during temperatures lower than 15°C, as this might delay drying time.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of July 10, 2025 – This release replaces all eventually earlier issued versions.