

DUPLI-COLOR profi Roughcast Spray

Technical Information

Creates an individual surface structure, similar to a rough plaster. It is an exclusive, water-based polyurethane dispersion, which is suitable to repair and adapt a textured plastering. It can be used on misc. surfaces, such as concrete, gypsum plasterboard, sheetrock, wood etc. Can be overcoated with all dispersion paints.

Ord.-no: 503719

Quality & properties

Quick and easy to use, perfect for wall repairs
Individual surface structure, small to medium grain size
Low in odour
Waterbased
Makes structures like roughplaster
For concrete, gypsum plasterboard, sheetrock, wood, wallpaper etc.

Physical & chemical data

Base: Polyurethane dispersion
Colourname: white
Degree of gloss: mat GU
Efficiency: 400 ML – 1,5 m²
Completely dry: 60 min
Overcoatable: 60 min
Surfaces: concrete, gypsum plasterboard, sheetrock, wood etc.
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Storage stability: 2 y
Content: 400 ML

How to use

The spray creates an individual structure of the surface, similar to a roughcast.
By several thicknesses and distances of spraying you can create a fine to medium graininess.
Exclusive, water-based polyurethane dispersion, suitable to repair and to align roughcast.
Waterproof.
Suitable for inside and outside use.
Suitable for application on many surfaces: concrete, gypsum plasterboard, sheetrock, wood etc.
Drying 60 minutes.
Overpaintable with all dispersion paints.
In case of spots of water, smoke and smut we recommend, to use first DUPLI-COLOR Isolating Primer.
please paint over with waterbased paint, to protect the structure.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EEC in the actually valid version.

As of May 21, 2025 – This release replaces all eventually earlier issued versions.