

DUPLI-COLOR SPOT BLENDER AUTOMOTIVE

Technical Information



Can be used anywhere in blended painting with clear paint and finish paint. With its special formula it dissolves the edge zones, creating a very fine distribution of paint in the transition zone. This means considerably less polishing. Ideal for spot repairs. Immediately after application, apply DUPLI-COLOR 2K Super clear paint, 2-coat clear paint, DUPLI-COLOR Auto Spray or DUPLI-COLOR Auto-Color on the transition zone in the blender area.

Ord.-no: 373060

Quality & properties

- Essential for spot coating
- Additional coating to DUPLI-COLOR Clear Coats and Auto-Sprays
- Simple time-saving processing
- Dissolves well
- Easy to polish
- Significantly reduces the need to polish
- Blends in seamlessly edge areas

Physical & chemical data

- Base: Special resin
- Colourname: transparent
- Dust dry: 10 min
- Completely dry: 24 h
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content: 150 ML

How to use

- Shake can.
- Test spray.
- Immediately after application of the lacquer, spray from a distance of 25 cm several thin coats into the outer zones.
- After curing the outer zone can be polished.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.