

## DUPLI-COLOR GLITTER SPRAY

## Technical Information



Special glitter painting for all kinds of surfaces e.g. glass, ceramics, stone, metals and all surfaces, which are painted with acrylic or nitro-combi lacquers. Also for wood (primed or painted); limited suitable on carton, paper and coatable plastics. The silver colour is transparent with glitter particles. The coloured shades are opaque with glitter particles. The effect you achieve depends strongly from color and quality of the surface.

**Ord.-no:** 685040, 684463, 669644, 685057, 684418, 332609, 669255, 685071, 684470, 669187, 685095, 684517, 669217, 685101, 684524, 669200, 685118, 684500, 669248, 685125, 684494, 669224, 338663

### Quality & properties

- High-grade nitro-combi quality
- Excellent adhesion
- Good flow, smooth surface
- Resistant to wiping
- Suitable for lacquering indoors and outdoors objects
- Weather-resistant, light-proof, UV-resistant
- Scratch-, shock- and impact-resistant

### Physical & chemical data

Base: Nitrocombi resin

Colourname:

- blue black
- gold
- silver transparent
- copper brown
- lime green
- marin blue
- purple
- violet

Degree of gloss: mat GU

Efficiency:

- 400 ML – 1.0 - 1.5 m<sup>2</sup>
- 200 ML – 0.5 - 0.7 m<sup>2</sup>
- 150 ML – 0.4 - 0.6 m<sup>2</sup>
- 400 ML – 0,5 - 0,7 m<sup>2</sup>

Dry to touch: 60 min

Dust dry: 10 min

Completely dry: 24 h

Overcoatable: 10 min

Surfaces: glass, ceramics, stone, metals and all surfaces, which acrylic or nitro-combi lacquers, wood, limited suitable on carton, paper and coatable plastics

Minimum Working Temperature: 10 °C

Maximum Working Temperature: 25 °C

Flash point: n.a.

Storage stability: 10 y

Content:

- 400 ML
- 200 ML
- 150 ML

### How to use

Remove flakes of old paint and rust.

The ground has to be clean, dry and free from fat.

Mask off areas not to be painted.

If necessary prime DUPLI-COLOR Primer. To achieve a covering layer of the effect, prime first Diamond Effect Gold with white Effect Primer and the other covering colours with black Effect Primer

Before use, shake can for 3 minutes.

Test spray at an invisible spot.

Spray in 2 minute intervals several thin coats from a distance of approx. 25 cm.

Do not spray over surfaces which are painted with synthetic resin lacquer!

The Diamond-effect strongly depends from colour of the ground. The silver-transparent product is best on painted or coloured objects. The same effect you achieve with the covering products marine, gold or blue-black on not-painted objects.

For durable resistance we recommend to apply a protective coat of DUPLI-COLOR Zapon Spray.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 21, 2025** – This release replaces all eventually earlier issued versions.