

## DUPLI-COLOR CAR'S RUST PROTECTIVE PRIMER

## Technical Information



The ideal primer for use as filler and as an adhesion promoter between surface and final coat. Coatable with air-drying acrylic-, synthetic and nitro-combi lacquers. For metal, wood, ceramics, stone, carton and others.

**Ord.-no:** 385889, 693847, 740220, 730221, 218194, 100009

### Quality & properties

- High-grade nitro-combi quality
- Especially high filling power
- Very good flow, smooth surface
- Quick-drying
- Protects from corrosion
- Promotes best adhesion of the top coat on the subsoil
- Optimizes the gloss of the top coat
- Grants the economical application of the top coat
- Especially user-friendly due to durable quality, which is easy to apply and easy to sand and re-coat
- For indoor and outdoor applications

### Physical & chemical data

- Base: Nitrocombi resin
- Colourname:
  - grey
  - red
  - white
- Degree of gloss: mat GU
- Efficiency:
  - 400 ML – 0.8 m<sup>2</sup>
  - 600 ML – 1.2 m<sup>2</sup>
  - 400 ML – 6 m<sup>2</sup>
- Dry to touch: 30 min
- Dust dry: 15 min
- Completely dry: 2-4 h
- Surfaces: metal, wood, ceramics, stone, carton and others
- Minimum Working Temperature:
  - 10 °C
  - 10
- Maximum Working Temperature:
  - 25 °C
  - 25
- Flash point: n.a.
- Storage stability: 10 y
- Content:
  - 400 ML
  - 600 ML

---

**How to use**

De-rust, sand and clean the surfaces to be painted.  
Apply putty, if necessary.  
The surface has to be clean, dry and free from rust and fat.  
Shake cans for 2 minutes.  
Test spray on an invisible spot  
Egalize little dents and porous repair spots by repeated spraying of thin layers and sanding.  
Spray from a distance of approx. 25 cm.  
After drying (approx. 2-4 hours), wet-sand with sandpaper (grain 600), clean the surface and let it dry.  
Afterwards apply the top coat.  
Coatable with synthetic or acrylic lacquers.  
Do not spray over synthetic lacquers!

**Environmentally sound**

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal**

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling**

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.