

DUPLI-COLOR RADIATOR SPRAY

Technical Information



Radiator Lacquer for renovating and repair of radiators, hot-water tanks, heating elements, warm water pipes etc.. Fast-drying, durably warmth- and gloss-resistant synthetic quality.

Ord.-no: 467165, 467141, 743887, 101420, 101421

Quality & properties

- High-grade synthetic quality
- High coverage and filling power
- Longterm durability and functionality
- Excellent adhesion
- Good flow, smooth surface
- Fast-drying
- Durable colour- and gloss retention
- Scratch-, bump- and impact-proof
- Heat-resistant up to 80°C

Physical & chemical data

Base: Alkyd resin

Colourname:

- creme white
- pure white
- black
- anthracite grey

Degree of gloss:

- gloss GU
- satin mat GU
- mat GU

Efficiency: 400 ML – 0.8 - 1.2 m²

Dry to touch:

- 3 h
- 3 min

Dust dry: 30 min

Completely dry:

- 24 h
- 24 min

Surfaces: radiators, hot-water tanks, heating elements, warm water pipes etc.

Minimum Working Temperature: 10 °C

Maximum Working Temperature: 25 °C

Flash point: n.a.

Storage stability: 10 y

Content: 400 ML

How to use

The surface has to be clean, dry and fat-free.
Remove flakes of old painting, then sand and prime.
The aerosol can should have room temperature.
Before use shake the can vigorously for 2-3 minutes.
Test colour of spray and compatibility of the lacquer at an invisible spot.
Spray several thin cross-coats from a distance of approx. 25 cm.
During application take care about good ventilation (but without draft) and carefully cover surrounding area.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.