

DUPLI-COLOR profi Degreaser Spray

Technical Information



Removes dirt, grease, oil, silicone, wax, tar, adhesive residues etc. Applicable to all surfaces like metal, plastic, glass and old paint. Economical dosage, easy, fast and residue-free application.

Ord.-no: 478376

Quality & properties

- Mild, non-aggressive solvent
- Simple, time-saving application
- Improves adhesion of subsequent coatings
- Very good efficiency
- Evaporation time: 60 sec/20°C

Physical & chemical data

- Base: Special combination
- Colourname: transparent
- Efficiency: 400 ML – 2,5 m²
- Surfaces: primed and filled areas, metal, glass, old paints and original paints from supplier, painted and unpainted surfaces
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Storage stability: 10 y
- Content: 400 ML

How to use

- Shake the can shortly before use
- 1 - 2 light coats, repeat if dirt excessive
- Wipe off with a clean, dry, non-woven cloth
- Allow cleaned surfaces to dry
- Wear an appropriate respirator (we recommend A2/P3)
- Suitable for all levelled, primed and filled surfaces, metal and glass, old and original paintwork and unpainted undercoats.
- Wear an appropriate respirator (we recommend A2/P3)

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 21, 2025 – This release replaces all eventually earlier issued versions.