

DUPLI-COLOR GRAFFITI-EX SPRAY

Technical Information



Highly effective paint stripper. Removes easily and thoroughly old paintings and undesired graffiti. To be applied on masonry, bricks, stone and concrete surfaces, marble, asphalt, glass, metal and wood surfaces.

Ord.-no: 195419

Quality & properties

Dissolves and removes lacquers and graffiti quickly and thoroughly
Becomes a consistency like gel, therefore it does not runoff on a vertical surface, but acts concentrated
Application on non-ferrous metals might cause discolouration
Ph-neutral

Physical & chemical data

Base: Special combination
Colourname: transparent
Efficiency: 400 ML – 0.8 m²
Dust dry: 24 h
Completely dry: 24 h
Overcoatable: 0 min
Surfaces: walls, clay bricks, stone and concrete surfaces, marble -, bitumen -, glass -, metal and wood surfaces
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Flash point: n.a.
Storage stability: 10 y
Content: 400 ML

How to use

Check the firmness and stability of the basic colour on painted or lacquered grounds at an inconspicuous spot. Sensitive areas, which you do not want to treat, should be covered carefully with a protective sheeting.
Shake can.
Spray generously and let act for approx. 10 - 15 minutes. Depending on quality and age of the paint you want to remove, the acting time can be shortened or extended up to 24 hours.
Then scrape off with a suitable tool.
If necessary, wash off with cellulose nitrate diluent or just with water.
In case of very porous grounds, use a wire brush.
If necessary, repeat the procedure.
Before application of new paint, all residues of Graffiti-ex have to be removed.
Attention: May not run into sewage system! Collect detached paints and dispose it as special waste!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 21, 2025 – This release replaces all eventually earlier issued versions.