

DUPLI-COLOR TUNING ALU WHEEL PAINT**Technical Information**

For lacquering and repair works in the most current aluminium shades, especially for alloy rims.

Ord.-no: 665653, 665585, 665660, 665592, 665677, 665615, 665691, 665646

Quality & properties

High-grade, quick-drying nitro-combi paint
Good flow, smooth surface
Weather-resistant, light-proof, UV-resistant (non-yellowing)
Limited fuel-resistance
Good colour- and gloss retention
Hard surface, abrasion-resistant

Physical & chemical data

Base: Nitrocombi resin
Colourname:

- argento
- viper
- arctic
- quartz

Smell: Characteristic
Degree of gloss value:

- semi mat, 25 ±5
- semi gloss, 45 ±5

Efficiency:

- 12 ML – small spots m²
- 150 ML – small spots m²

Dust dry: 10 min
Dry to touch: 30 min
Completely dry: 24 h
Overcoatable: 30 min
Surfaces: aluminium shades
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Flash point:

- 27 °C
- n.a.

Storage stability: 10 years
Content:

- 12 ML
- 150 ML

How to use

Carefully clean rims from dirt, fat and brake-dust.
Treat existing pore rust with presto Deruster.
The ground has to be sanded, clean, dry and fat-free.
Mask off the rim edges with masking tape.
Use paper to protect surrounding area from spray-dust.
Prime with DUPLI-COLOR Primer.
After drying, slightly sand (sanding paper grain P600)
Before use, shake the can vigorously for 3 minutes.
Test spray to check colour-matching.
Spray several thin coats in 3 - 5 minute intervals from a distance of approx. 25 cm.
After 30 minutes drying time, coat with DUPLI-COLOR TUNING WHEEL PAINT Clear Coat to protect the metal pigments in the lacquer.
Do not spray over synthetic paints!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of July 10, 2025 – This release replaces all eventually earlier issued versions.