

DUPLI-COLOR TUNING DIAMOND**Technical Information**

Special glitter painting for high-value designs, e.g. on consoles or door coverings on all kinds of surfaces. With silver glitter particles to be applied on colored surfaces. Colored fulltones for covering paintings. The effect you achieve depends strongly from color and quality of the surface.

Ord.-no: 665486, 665257, 665332

Quality & properties

High-grade nitro-combi quality
Excellent adhesion
Good flow, smooth surface
Resistant to wiping
Suitable for lacquering indoors and outdoors objects
Weather-resistant, light-proof, UV-resistant
Scratch-, shock- and impact-resistant

Physical & chemical data

Base: Nitrocombi resin
Colourname:

- blue black
- blue
- transparent silver

Efficiency: 150 ML – 0.6 m²
Dust dry: 10 min
Completely dry: 24 h
Overcoatable: 10 min
Surfaces: glass, ceramics, stone, metal, wood, limited suitable on carton, paper and coatable plastics
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Flash point: n.a.
Storage stability: 10 y
Content: 150 ML

How to use

Remove flakes of old paint and rust.

The ground has to be clean, dry and free from fat.

Mask off areas not to be painted.

If necessary prime DUPLI-COLOR Primer. To achieve a covering layer of the effect, prime first Diamond Effect Gold with white Effect Primer and the other covering colours with black Effect Primer

Before use, shake can for 3 minutes.

Test spray at an invisible spot.

Spray in 2 minute intervals several thin coats from a distance of approx. 25 cm.

Do not spray over surfaces which are painted with synthetic resin lacquer!

The Diamond-effect strongly depends from colour of the ground. The silver-transparent product is best on painted or coloured objects. The same effect you achieve with the covering products marine, gold or blue-black on not-painted objects.

For durable resistance we recommend to apply a protective coat of DUPLI-COLOR Zapon Spray.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.