

DUPLI-COLOR SPOTMARKER FOR FORESTRY

Technical Information



Special spray lacquer with sprayhead and integrated capillary tube as well as coloured donut. Ideal for markings and writings on tree-trunks and all kinds of wood as well as for markings on streets and buildings. High covering and intensive shining. Excellent adherence even on humid surfaces. Optional accessory: metal spray actuator for comfortable use. For temporary markings.

Ord.-no: 634765, 642876, 642883, 642890, 642906, 695094, 634772

Quality & properties

Special spray nozzle for plane applications and also for targeted writing
Excellent adhesion even on humid surfaces
Markings shine bright for 6 - 9 months
Excellent covering quality grants high efficiency
Intensive luminance of the fluorescent shades
Environmentally sound and not hazardous to health
Safe during frost up to -10°
Self-cleaning valve

Physical & chemical data

Base: Acrylic resin
Colourname:

- neon red
- neon yellow
- orange
- green
- blue
- black
- white

Efficiency: 500 ML – 140 m
Dry to touch: 30 min
Dust dry: 10 min
Completely dry: 24 min
Overcoatable: 24 h
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Flash point: n.a.
Storage stability: 10 y
Content: 500 ML

How to use

Shake can for approx. 3 minutes.
Test spray at an invisible spot.
Spray distance approx. 25 cm.
Apply the desired marking.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.