

## DUPLI-COLOR CEMENT LOOK

## Technical Information



Fast-drying cement-effect. For applications on all kinds of surfaces. Depending on layer thickness, it is possible to achieve different drying-conditions, like real cement. By spraying a last fine mist, it's even possible to achieve a mineral feel. Please use mat clear coat for outdoor using.

**Ord.-no:** 521621, 521638

### Quality & properties

Polystyrene-resistant acrylic lacquer with a special solvent  
 Very good coverage  
 Excellent adhesion on many materials, e.g. polystyrene, metal, wood, glass, ceramics, eternite, concrete, stone, paper, cardboard, coatable hard plastics, flowers etc.  
 Good flow, smooth surface  
 Dries quick and evenly  
 Suitable for painting and repairing indoors and outdoors objects  
 Resistant to wiping  
 Weather-resistant, light-proof, UV-resistant  
 Scratch-, bump- and shock-proof

### Physical & chemical data

Base: Acrylate copolymers  
 Colourname: grey  
 Degree of gloss: mat GU  
 Efficiency: 400 ML – 1 m<sup>2</sup>  
 Dry to touch: 30 min  
 Dust dry: 10 min  
 Completely dry: 24 h  
 Surfaces: polystyrene, metal, wood, glass, ceramics, eternite, concrete, stone, paper, cardboard, coatable hard plastics, flowers.  
 Minimum Working Temperature: 10 °C  
 Maximum Working Temperature: 25 °C  
 Flash point: n.a.  
 Temperature Resistance: 80 °C  
 Storage stability: 10 y  
 Content: 400 ML

### How to use

Remove rust and dirt.  
 The ground has to be clean, dry and free from fat.  
 Possibly existing old paintings and smooth surfaces have to be roughened with fine sand paper.  
 Mask off areas not to be painted.  
 Before use, shake can for 3 minutes.  
 Test spray at an invisible spot.  
 Spray from a distance of approx. 25 cm several thin coats.  
 Do not spray over surfaces which are painted with synthetic resin lacquer!

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.