

DUPLI-COLOR CEMENT LOOK

Technical Information



Fast-drying cement-effect. For applications on all kinds of surfaces. Depending on layer thickness, it is possible to achieve different drying-conditions, like real cement. By spraying a last fine mist, it's even possible to achieve a mineral feel. Please use mat clear coat for outdoor using.

Ord.-no: 521621, 521638

Quality & properties

Polystyrene-resistant acrylic lacquer with a special solvent
 Very good coverage
 Excellent adhesion on many materials, e.g. polystyrene, metal, wood, glass, ceramics, eternite, concrete, stone, paper, cardboard, coatable hard plastics, flowers etc.
 Good flow, smooth surface
 Dries quick and evenly
 Suitable for painting and repairing indoors and outdoors objects
 Resistant to wiping
 Weather-resistant, light-proof, UV-resistant
 Scratch-, bump- and shock-proof

Physical & chemical data

Base: Acrylate copolymers
 Colourname:
 ◦ grey
 ◦ hoover dark grey
 Degree of gloss: mat GU
 Efficiency: 400 ML – 1 m²
 Dry to touch: 30 min
 Dust dry: 10 min
 Completely dry: 24 h
 Surfaces: polystyrene, metal, wood, glass, ceramics, eternite, concrete, stone, paper, cardboard, coatable hard plastics, flowers.
 Minimum Working Temperature: 10 °C
 Maximum Working Temperature: 25 °C
 Flash point: n.a.
 Temperature Resistance: 80 °C
 Storage stability: 10 y
 Content: 400 ML

How to use

Remove rust and dirt.
The ground has to be clean, dry and free from fat.
Possibly existing old paintings and smooth surfaces have to be roughened with fine sand paper.
Mask off areas not to be painted.
Before use, shake can for 3 minutes.
Test spray at an invisible spot.
Spray from a distance of approx. 25 cm several thin coats.
Do not spray over surfaces which are painted with synthetic resin lacquer!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 21, 2025 – This release replaces all eventually earlier issued versions.