

DUPLI-COLOR ANTI SLIP SPRAY

Technical Information



Special spray paint based on modified acrylic resins with non-slip particles, transparent silk matt. Increases grip on slippery and damp surfaces as well as on handrails and tool handles indoors and outdoors. Reduces the risk of falls and increases safety on e.g. Stairs, shower trays, bathroom floors, pool edges, balconies, boats and walkable areas in general.

Ord.-no: 419096

Quality & properties

Increases the security conditions on e.g. Stairs, bathroom floors, pool edges, balconies and boats.
Chlorine and salt water resistant
Good adhesion to concrete, asphalt, tiles, wood, metal, linoleum and most plastics.
Easy to use thanks to the overhead valve
Quick drying
Use in indoor- and outdoor areas
Transparent semi-gloss

Physical & chemical data

Base: Acrylic resin
Colourname: transparent mat
Degree of gloss: mat GU
Efficiency: 400 ML – 1,6 m²
Dry to touch: 30 min
Dust dry: 5 min
Completely dry: 24 h
Overcoatable: 1-2 h
Surfaces: concrete, asphalt, tile, wood, metal, linoleum and most plastics
Minimum Working Temperature: 15 °C
Maximum Working Temperature: 25 °C
Storage stability: 10 y
Content: 400 ML

How to use

Processing temperature 15-25 ° C.
The surface must be clean, dry and free of grease.
Cover areas not to be painted.
Shake can for 2 minutes before use.
Turn the can upside down to use.
test spray
Apply in several thin layers.
Allow to flash off for 5 minutes between layers.
The structure depends on the spray distance and the number of layers.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.