

## DUPLI-COLOR VINTAGE LOOK

## Technical Information



DUPLI-COLOR VINTAGE LOOK is a chalk-effect spray for decoration purposes. It makes a mat finish. In the fields of decoration, furnishing, design, restauration or interior fittings more beautiful living is actually connected with the orientation to weathered shabby chic. Whether vitrines, chests, pictures frames, tables, decorative objects, suitcases or caskets - they all are trimmed to an individual old or used look.

**Ord.-no:** 466007, 466090, 466106, 466113, 466120, 466137, 466144, 466007-DG, 466007-DW, 466090-DG, 466090-DW, 466106-DG, 466106-DW, 466113-DG, 466113-DW, 466120-DG, 466120-DW, 466137-DG, 466137-DW, 466144-DG, 466144-DW

### Quality & properties

Environmentally friendly with low solvent content  
Less spray mist, therefore pleasant usage even indoors  
Not only for indoor, but also suitable for outdoor applications  
Suitable for use on polystyrene  
Flaws made during spraying can be corrected within 10 minutes after application. Within this space time the "open" paint layer can be washed off with water and soap  
Do not spray over synthetic paints

### Physical & chemical data

Base: Waterbased acrylic resin  
Colourname:  

- white
- sahara
- kalahari pink
- blue
- mojave
- grey
- karakum

Degree of gloss: mat GU  
Efficiency: 400 ML – 1.0 - 1.4 m<sup>2</sup>  
Dry to touch: 20 min  
Dust dry: 10 min  
Completely dry: 12 h  
Overcoatable: 10 min  
Surfaces: vitrines, chests, pictures frames, tables, decorative objects, suitcases or caskets  
Minimum Working Temperature: 10 °C  
Maximum Working Temperature: 25 °C  
Flash point: n.a.  
Storage stability: 4 y  
Content: 400 ML

---

### How to use

The surface must be clean, absolutely fat-free and dry.  
Remove loose parts.  
In spite of low formation of spray mist, we recommend to protect the surrounding area.  
If necessary, remove or sand old paint layers.  
Shake can for approx. 3 minutes.  
Test spray at an invisible spot.  
The optimal distance to spray is approx. 25 cm.  
Spray several thin layers in 2 minute intervals.  
After spraying turn the can upside down and press sprayhead to empty the valve.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.