

DUPLI-COLOR profi Paint Stripper**Technical Information**

Highly effective paint remover. Removes old coats of paint on stone, concrete, brickwork, tarmac, metal and wood.

Ord.-no: 478345

Quality & properties

Gel structure adheres also on vertical surfaces
Thorough and quick
Economical proportioning
Easy to use

Physical & chemical data

Base: Special combination
Colourname: transparent
Efficiency: 400 ML – 0.8 m²
Surfaces: wood, glass, brickwork, clinker, stone, concrete, tarmac, metal
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Flash point: n.a.
Storage stability: 10 y
Content: 400 ML

How to use

Bring can to room temperature.
Operating temperature 5° to 30° C.
Shake for 2 minutes before use.
Before use, test the compatibility of the surface.
Apply Paint Remover generously and allow to take effect.
Residence time approx. 15 min (depends on the quality and the age of the removing paint).
Then remove with an appropriate tool. When required, repeat the treatment.
Contaminated Paint Remover should be regarded as chemical waste.
Wear an appropriate respirator (we recommend A2/P3).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.