

Safety data sheet
according to UK REACH

Printing date 17.03.2025

Version number 8 (replaces version 7)

Revision: 04.02.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name:** DUPLI-COLOR AEROSOL ART Clearcoat

· **Article number:** 744037, 744044

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Sector of Use**

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Product category** PC9a Coatings and paints, thinners, paint removers

· **Process category**

PROC7 Industrial spraying

PROC11 Non industrial spraying

· **Application of the substance / the mixture** Clear coating material, Varnish

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

European Aerosols GmbH*

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@europaean-aerosols.com

European Aerosols Ltd.

Wilberforce House

Station Road

London NW4 4QE,

phone no. +44 1223 790332

*Formerly known as Motip Dupli GmbH

· **Further information obtainable from:** Department Product Safety

· **1.4 Emergency telephone number:**

Tel.: +49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergency phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland:

Poison center if child has been poisoned: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

GB

(Contd. on page 2)

Safety data sheet according to UK REACH

Printing date 17.03.2025

Version number 8 (replaces version 7)

Revision: 04.02.2025

Trade name: DUPLI-COLOR AEROSOL ART Clearcoat

(Contd. of page 1)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



GHS02



GHS07

- Signal word Danger
- Hazard-determining components of labelling:
acetone
2-methoxy-1-methylethyl acetate
Hydrocarbons, C9, aromatics
n-butyl acetate

- Hazard statements
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents / container in accordance with regional regulations.

- Additional information:
EUH066 Repeated exposure may cause skin dryness or cracking.
Buildup of explosive mixtures possible without sufficient ventilation.

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

GB

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 17.03.2025

Version number 8 (replaces version 7)

Revision: 04.02.2025

Trade name: DUPLI-COLOR AEROSOL ART Clearcoat

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	12.5-<20%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas 1A, H220 Press. Gas (Comp.), H280	12.5-<20%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	5-<10%
EC number: 905-588-0 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	reaction mass of ethylbenzene and xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336 EUH066	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas 1A, H220 Press. Gas (Comp.), H280	2.5-<5%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	2.5-<5%

Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex IA 1272/2008 EU), so the classification as carcinogen need not to apply.

xylene: Contains ethylbenzene CAS 100-41-4

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Generally the product does not irritate the skin.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)

Safety data sheet

according to UK REACH

Printing date 17.03.2025

Version number 8 (replaces version 7)

Revision: 04.02.2025

Trade name: DUPLI-COLOR AEROSOL ART Clearcoat

(Contd. of page 3)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters -**
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppm

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 17.03.2025

Version number 8 (replaces version 7)

Revision: 04.02.2025

Trade name: DUPLI-COLOR AEROSOL ART Clearcoat

(Contd. of page 4)

106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm
 Long-term value: 1450 mg/m³, 600 ppm
 Carc (if more than 0.1% of buta-1.3-diene)

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm
 Long-term value: 274 mg/m³, 50 ppm
 Sk

reaction mass of ethylbenzene and xylene

WEL Short-term value: 441 mg/m³, 100 ppm
 Long-term value: 220 mg/m³, 50 ppm
 Sk; BMGV

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
 Long-term value: 724 mg/m³, 150 ppm

· DNELs**67-64-1 acetone**

Oral	DNEL	62 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	62 mg/kg /per day (Consumer, longterm systemic)
	DNEL	186 mg/kg /per day (Worker, longterm systemic)
Inhalative	DNEL	2420 mg/m ³ (Worker, acute local)
	DNEL	1210 mg/m ³ (Worker, longterm systemic)
	DNEL	200 mg/m ³ (Consumer, longterm systemic)
	DNEL	60 mg/m ³

108-65-6 2-methoxy-1-methylethyl acetate

Dermal	DNEL	796 mg/kg /per day (Worker, longterm systemic)
	DNEL	320 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	275 mg/m ³ (Worker, longterm systemic)
	DNEL	33 mg/m ³ (Consumer, longterm systemic)

reaction mass of ethylbenzene and xylene

Oral	DNEL	1.6 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	180 mg/kg /per day (Worker, longterm systemic)
Inhalative	DNEL	211 mg/m ³ (Worker, longterm systemic)
	DNEL	221 mg/m ³ (Worker, longterm local)
	DNEL	442 mg/m ³ (Worker, acute systemic)
	DNEL	289 mg/m ³ (Worker, acute local)
	DNEL	14.8 mg/m ³ (Consumer, longterm systemic)
	DNEL	260 mg/m ³ (Consumer; acute systemic)
	DNEL	65.3 mg/m ³ (Consumer, longterm local)
	DNEL	260 mg/m ³ (Consumer, acute local)

Hydrocarbons, C9, aromatics

Oral	DNEL	11 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	25 mg/kg /per day (Worker, longterm systemic)
	DNEL	11 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	150 mg/m ³ (Worker, longterm systemic)
	DNEL	32 mg/m ³ (Consumer, longterm systemic)

123-86-4 n-butyl acetate

Oral	DNEL	2 mg/kg /per day (Consumer, longterm systemic)
------	------	--

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 17.03.2025

Version number 8 (replaces version 7)

Revision: 04.02.2025

Trade name: DUPLI-COLOR AEROSOL ART Clearcoat

(Contd. of page 5)

<i>Dermal</i>	<i>DNEL</i>	2 mg/kg /per day (Consumer, acute systemic)
	<i>DNEL</i>	11 mg/kg /per day (Worker, longterm systemic)
	<i>DNEL</i>	11 mg/kg /per day (Worker, acute systemic)
	<i>DNEL</i>	6 mg/kg /per day (Consumer, longterm systemic)
	<i>DNEL</i>	6 mg/kg /per day (Consumer, acute systemic)
<i>Inhalative</i>	<i>DNEL</i>	300 mg/m3 (Worker, longterm systemic)
	<i>DNEL</i>	600 mg/m3 (Worker, acute systemic)
	<i>DNEL</i>	300 mg/m3 (Worker, longterm local)
	<i>DNEL</i>	600 mg/m3 (Worker, acute local)
	<i>DNEL</i>	35.7 mg/m3 (Consumer, longterm systemic)
	<i>DNEL</i>	300 mg/m3 (Consumer; acute systemic)
	<i>DNEL</i>	35.7 mg/m3 (Consumer, longterm local)
	<i>DNEL</i>	

· **PNECs****67-64-1 acetone**

<i>PNEC</i>	10.6 mg/l (Freshwater)
<i>PNEC</i>	1.06 mg/l (Seawater)
<i>PNEC</i>	21 mg/l (Sporadic release)
<i>PNEC</i>	100 mg/l (Sewage treatment plant)
<i>PNEC</i>	30.4 mg/kg (Freshwater sediment)
<i>PNEC</i>	3.04 mg/kg (Seawater sediment)
<i>PNEC</i>	29.5 mg/kg (Soil)

108-65-6 2-methoxy-1-methylethyl acetate

<i>PNEC</i>	0.635 mg/l (Freshwater)
<i>PNEC</i>	0.064 mg/l (Seawater)
<i>PNEC</i>	100 mg/l (Sewage treatment plant)
<i>PNEC</i>	3.29 mg/kg (Freshwater sediment)
<i>PNEC</i>	0.329 mg/kg (Seawater sediment)
<i>PNEC</i>	0.29 mg/kg (Soil)

123-86-4 n-butyl acetate

<i>PNEC</i>	0.18 mg/l (Freshwater)
<i>PNEC</i>	0.018 mg/l (Seawater)
<i>PNEC</i>	0.36 mg/l (Sporadic release)
<i>PNEC</i>	35.6 mg/l (Sewage treatment plant)
<i>PNEC</i>	0.981 mg/kg (Freshwater sediment)
<i>PNEC</i>	0.0981 mg/kg (Seawater sediment)
<i>PNEC</i>	0.0903 mg/kg (Soil)

· **Ingredients with biological limit values:****reaction mass of ethylbenzene and xylene**

<i>BMGV</i>	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**· **Appropriate engineering controls** No further data; see section 7.· **Individual protection measures, such as personal protective equipment**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 17.03.2025

Version number 8 (replaces version 7)

Revision: 04.02.2025

Trade name: DUPLI-COLOR AEROSOL ART Clearcoat

(Contd. of page 6)

*Immediately remove all soiled and contaminated clothing**Wash hands before breaks and at the end of work.**Do not inhale gases / fumes / aerosols.**Avoid contact with the eyes and skin.**Avoid contact with the eyes.***· Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

*Filter A2/P3***· Hand protection***Protective gloves***· Material of gloves***Butyl rubber, BR*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material*Butyl rubber gloves with a thickness of 0.4 mm are resistant to:**Acetone: 480 min**Butyl acetate: 60 min**Ethyl acetate: 170 min**Xylene: 42 min*

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· Eye/face protection*Tightly sealed goggles*

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties**· General Information****· Physical state***Aerosol***· Colour:***According to product specification***· Odour:***Characteristic***· Odour threshold:***Not determined.***· Melting point/freezing point:***Undetermined.***· Boiling point or initial boiling point and boiling range***Not applicable, as aerosol.***· Flammability***Not applicable.***· Lower and upper explosion limit****· Lower:**

1.5 Vol % (106-97-8 butane (containing < 0,1 % butadiene (203-450-8)))

· Upper:*13 Vol % (67-64-1 acetone)***· Flash point:***Not applicable, as aerosol.***· Auto-ignition temperature:**

333 °C (631.4 °F) (108-65-6 2-methoxy-1-methylethyl acetate)

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 17.03.2025

Version number 8 (replaces version 7)

Revision: 04.02.2025

Trade name: DUPLI-COLOR AEROSOL ART Clearcoat

(Contd. of page 7)

· Decomposition temperature:	Not determined.
· pH	Mixture is non-soluble (in water).
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C (68 °F):	8300 hPa (6225.5 mm Hg) (74-98-6 propane)
· Vapour pressure at 50 °C (122 °F):	16500 hPa (12376 mm Hg)
· Density and/or relative density	
· Density at 20 °C (68 °F):	0.7 g/cm ³ (5.8 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information	
· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Explosive properties:	Not determined.
· Solvent content:	
· Organic solvents:	88.5 %
· VOC (EC)	---
	645.0 g/l
· VOC-EU%	89.00 %
· Solids content:	10.6 %
· Change in condition	
· Evaporation rate	Not applicable.

· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.

(Contd. on page 9)

Safety data sheet

according to UK REACH

Printing date 17.03.2025

Version number 8 (replaces version 7)

Revision: 04.02.2025

Trade name: DUPLI-COLOR AEROSOL ART Clearcoat

(Contd. of page 8)

- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	>15800 mg/kg (rabbit)
Inhalative	LC50 / 4h	76 mg/l (rat)
	LC50 / 96 h	5540 mg/l (oncorhynchus mykiss)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8530 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>10000 mg/m3 (rat)

reaction mass of ethylbenzene and xylene

Oral	LD50	3523 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	29000 mg/m3 (rat)

Hydrocarbons, C9, aromatics

Oral	LD50	>5000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2000 mg/kg (rab) (OECD 402)

123-86-4 n-butyl acetate

Oral	LD50	10800 mg/kg (rat) (OECD 401)
Dermal	LD50	>17600 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>21 mg/m3 (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

67-64-1 acetone

LC50/96h	8300 mg/l (fish)
EC50/96h	7200 mg/l (algae)
LC50 / 48 h	8450 mg/l (crustacean (water flea))

108-65-6 2-methoxy-1-methylethyl acetate

EC50 / 48 h	>500 mg/l (daphnia magna)
LC50 / 96 h	100-180 mg/l (oncorhynchus mykiss)

(Contd. on page 10)

Safety data sheet according to UK REACH

Printing date 17.03.2025

Version number 8 (replaces version 7)

Revision: 04.02.2025

Trade name: DUPLI-COLOR AEROSOL ART Clearcoat

(Contd. of page 9)

reaction mass of ethylbenzene and xylene

EC50 / 48 h 7.4 mg/l (daphnia magna)

LC50 / 96 h 13.5 mg/l (fish)

Hydrocarbons, C9, aromatics

EC50 / 48 h 302 mg/l (daphnia magna)

EC50 / 72 h 2.75 mg/l (Pseudokirchneriella subcapitata)

EC50 / 96 h 9.2 mg/l (Regenbogenforelle)

- **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

- **12.7 Other adverse effects**

- **Remark:** Harmful to fish

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN number or ID number**

- **ADR, IMDG, IATA**

UN1950

- **14.2 UN proper shipping name**

- **ADR**

1950 AEROSOLS

- **IMDG**

AEROSOLS

- **IATA**

AEROSOLS, flammable

- **14.3 Transport hazard class(es)**

- **ADR**



- **Class**

2 5F Gases.

(Contd. on page 11)

Safety data sheet according to UK REACH

Printing date 17.03.2025

Version number 8 (replaces version 7)

Revision: 04.02.2025

Trade name: DUPLI-COLOR AEROSOL ART Clearcoat

(Contd. of page 10)

· **Label** 2.1· **IMDG, IATA**· **Class** 2.1 Gases.· **Label** 2.1· **14.4 Packing group**· **ADR, IMDG, IATA** not regulated· **14.5 Environmental hazards:** Not applicable.· **14.6 Special precautions for user** Warning: Gases.· **Hazard identification number (Kemler code):** -· **EMS Number:** F-D,S-U· **Stowage Code**

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· **Segregation Code**

SG69 For AEROSOLS with a maximum capacity of 1 litre:

Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**· **ADR**· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **Transport category**

2

· **Tunnel restriction code**

D

· **IMDG**· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":**

UN 1950 AEROSOLS, 2.1

*

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Poisons Act**· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

(Contd. on page 12)

GB

Safety data sheet

according to UK REACH

Printing date 17.03.2025

Version number 8 (replaces version 7)

Revision: 04.02.2025

Trade name: DUPLI-COLOR AEROSOL ART Clearcoat

(Contd. of page 11)

· Reportable explosives precursors

67-64-1 acetone

Listed

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU**· Named dangerous substances - ANNEX I** None of the ingredients is listed.**· Seveso category P3a** FLAMMABLE AEROSOLS**· Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t**· Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t**· 15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

Data is based on internal technical data and technical data from suppliers.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

(Contd. on page 13)

Safety data sheet
according to UK REACH

Printing date 17.03.2025

Version number 8 (replaces version 7)

Revision: 04.02.2025

Trade name: DUPLI-COLOR AEROSOL ART Clearcoat

(Contd. of page 12)

*Asp. Tox. 1: Aspiration hazard – Category 1**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3****. * Data compared to the previous version altered.***

GB