

## Safety data sheet according to UK REACH

Printing date 17.04.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### · 1.1 Product identifier

· **Trade name:** DUPLI-COLOR ELOXAL SPRAY various colours

· **Article number:** 299780, 299797, 299803, 299810, 323003, 584107alt

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

#### · **Sector of Use**

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Product category** PC9a Coatings and paints, thinners, paint removers

#### · **Process category**

PROC7 Industrial spraying

PROC11 Non industrial spraying

· **Application of the substance / the mixture** Lacquer

#### · 1.3 Details of the supplier of the safety data sheet

##### · **Manufacturer/Supplier:**

European Aerosols GmbH\*

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@european-aerosols.com

European Aerosols Ltd.

Wilberforce House

Station Road

London NW4 4QE,

phone no. +44 1223 790332

\*Formerly known as Motip Dupli GmbH

· **Further information obtainable from:** Department Product Safety

#### · 1.4 Emergency telephone number:

Tel.: +49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergency phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland:

Poison center if child has been poisoned: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

GB

(Contd. on page 2)

# Safety data sheet according to UK REACH

Printing date 17.04.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

Trade name: **DUPLI-COLOR ELOXAL SPRAY** various colours

(Contd. of page 1)

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.  
STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02



GHS07

- **Signal word** *Danger*
- **Hazard-determining components of labelling:**  
acetone  
n-butyl acetate  
2-methoxy-1-methylethyl acetate
- **Hazard statements**  
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.
- **Precautionary statements**  
P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe spray.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of contents / container in accordance with regional regulations.
- **Additional information:**  
EUH066 Repeated exposure may cause skin dryness or cracking.  
Buildup of explosive mixtures possible without sufficient ventilation.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

GB

## Safety data sheet according to UK REACH

Printing date 17.04.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

**Trade name: DUPLI-COLOR ELOXAL SPRAY various colours**

(Contd. of page 2)

**· Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	25-<50%
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37	dimethyl ether ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	12.5-<20%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-<12.5%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336 EUH066	10-<12.5%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	2.5-<5%
CAS: 9004-70-0	cellulose nitrate ⚠ Expl. 1.1, H201	2.5-<5%
EC number: 905-588-0 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	reaction mass of ethylbenzene and xylene ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<2.5%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43	ethanol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	<2.5%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide ⚠ Carc. 2, H351	≤0.5%

**· Additional information:**

xylene: Contains ethylbenzene CAS 100-41-4

CAS 9004-70-0: GB CLP Note T

For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****· 4.1 Description of first aid measures****· General information:** Take affected persons out into the fresh air.**· After inhalation:** Supply fresh air; consult doctor in case of complaints.

(Contd. on page 4)

## Safety data sheet according to UK REACH

Printing date 17.04.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

**Trade name: DUPLI-COLOR ELOXAL SPRAY various colours**

(Contd. of page 3)

- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.  
Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters -**
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Do not inhale explosion gases or combustion gases.  
Mouth respiratory protective device.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.  
Keep away from ignition sources.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Keep away from heat and direct sunlight.  
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).  
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B

(Contd. on page 5)

## Safety data sheet according to UK REACH

Printing date 17.04.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

**Trade name: DUPLI-COLOR ELOXAL SPRAY various colours**

(Contd. of page 4)

· 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

##### · Ingredients with limit values that require monitoring at the workplace:

###### 67-64-1 acetone

WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm  
Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

###### 115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 766 mg/m<sup>3</sup>, 400 ppm

###### 123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

###### 106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm  
Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm  
Carc (if more than 0.1% of buta-1.3-diene)

###### 108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 274 mg/m<sup>3</sup>, 50 ppm  
Sk

###### reaction mass of ethylbenzene and xylene

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk; BMGV

###### 64-17-5 ethanol

WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm

###### 13463-67-7 titanium dioxide

WEL Long-term value: 10\* 4\*\* mg/m<sup>3</sup>  
\*total inhalable \*\*respirable

#### · DNELs

##### 67-64-1 acetone

Oral	DNEL	62 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	62 mg/kg /per day (Consumer, longterm systemic)
	DNEL	186 mg/kg /per day (Worker, longterm systemic)
Inhalative	DNEL	2420 mg/m <sup>3</sup> (Worker, acute local)
	DNEL	1210 mg/m <sup>3</sup> (Worker, longterm systemic)
	DNEL	200 mg/m <sup>3</sup> (Consumer, longterm systemic)
	DNEL	60 mg/m <sup>3</sup>

##### 123-86-4 n-butyl acetate

Oral	DNEL	2 mg/kg /per day (Consumer, longterm systemic)
	DNEL	2 mg/kg /per day (Consumer, acute systemic)
Dermal	DNEL	11 mg/kg /per day (Worker, longterm systemic)
	DNEL	11 mg/kg /per day (Worker, acute systemic)
	DNEL	6 mg/kg /per day (Consumer, longterm systemic)
	DNEL	6 mg/kg /per day (Consumer, acute systemic)
	DNEL	300 mg/m <sup>3</sup> (Worker, longterm systemic)

(Contd. on page 6)

## Safety data sheet according to UK REACH

Printing date 17.04.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

**Trade name: DUPLI-COLOR ELOXAL SPRAY various colours**

(Contd. of page 5)

	DNEL	600 mg/m <sup>3</sup> (Worker, acute systemic)
	DNEL	300 mg/m <sup>3</sup> (Worker, longterm local)
	DNEL	600 mg/m <sup>3</sup> (Worker, acute local)
	DNEL	35.7 mg/m <sup>3</sup> (Consumer, longterm systemic)
	DNEL	300 mg/m <sup>3</sup> (Consumer; acute systemic)
	DNEL	35.7 mg/m <sup>3</sup> (Consumer, longterm local)

**108-65-6 2-methoxy-1-methylethyl acetate**

Dermal	DNEL	796 mg/kg /per day (Worker, longterm systemic)
	DNEL	320 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	275 mg/m <sup>3</sup> (Worker, longterm systemic)
	DNEL	33 mg/m <sup>3</sup> (Consumer, longterm systemic)

**reaction mass of ethylbenzene and xylene**

Oral	DNEL	1.6 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	180 mg/kg /per day (Worker, longterm systemic)
Inhalative	DNEL	211 mg/m <sup>3</sup> (Worker, longterm systemic)
	DNEL	221 mg/m <sup>3</sup> (Worker, longterm local)
	DNEL	442 mg/m <sup>3</sup> (Worker, acute systemic)
	DNEL	289 mg/m <sup>3</sup> (Worker, acute local)
	DNEL	14.8 mg/m <sup>3</sup> (Consumer, longterm systemic)
	DNEL	260 mg/m <sup>3</sup> (Consumer; acute systemic)
	DNEL	65.3 mg/m <sup>3</sup> (Consumer, longterm local)
	DNEL	260 mg/m <sup>3</sup> (Consumer, acute local)

**64-17-5 ethanol**

Oral	DNEL	87 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	343 mg/kg /per day (Worker, longterm systemic)
	DNEL	206 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	950 mg/m <sup>3</sup> (Worker, longterm systemic)
	DNEL	1900 mg/m <sup>3</sup> (Worker, acute local)
	DNEL	114 mg/m <sup>3</sup> (Consumer, longterm systemic)
	DNEL	950 mg/m <sup>3</sup> (Consumer, acute local)

**· PNECs****67-64-1 acetone**

PNEC	10.6 mg/l (Freshwater)
PNEC	1.06 mg/l (Seawater)
PNEC	21 mg/l (Sporadic release)
PNEC	100 mg/l (Sewage treatment plant)
PNEC	30.4 mg/kg (Freshwater sediment)
PNEC	3.04 mg/kg (Seawater sediment)
PNEC	29.5 mg/kg (Soil)

**123-86-4 n-butyl acetate**

PNEC	0.18 mg/l (Freshwater)
PNEC	0.018 mg/l (Seawater)
PNEC	0.36 mg/l (Sporadic release)
PNEC	35.6 mg/l (Sewage treatment plant)
PNEC	0.981 mg/kg (Freshwater sediment)
PNEC	0.0981 mg/kg (Seawater sediment)

(Contd. on page 7)

# Safety data sheet

## according to UK REACH

Printing date 17.04.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

**Trade name: DUPLI-COLOR ELOXAL SPRAY various colours**

(Contd. of page 6)

PNEC	0.0903 mg/kg (Soil)
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>	
PNEC	0.635 mg/l (Freshwater)
PNEC	0.064 mg/l (Seawater)
PNEC	100 mg/l (Sewage treatment plant)
PNEC	3.29 mg/kg (Freshwater sediment)
PNEC	0.329 mg/kg (Seawater sediment)
PNEC	0.29 mg/kg (Soil)
<b>64-17-5 ethanol</b>	
PNEC	0.96 mg/l (Freshwater)
PNEC	0.79 mg/l (Seawater)
PNEC	2.75 mg/l (Sporadic release)
PNEC	580 mg/l (Sewage treatment plant)
PNEC	3.6 mg/kg (Freshwater sediment)
PNEC	2.9 mg/kg (Seawater sediment)
PNEC	0.63 mg/kg (Soil)
<b>Ingredients with biological limit values:</b>	
<b>reaction mass of ethylbenzene and xylene</b>	
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Do not eat, drink, smoke or sniff while working.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· **Hand protection**



Protective gloves

· **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

(Contd. on page 8)

# Safety data sheet

## according to UK REACH

Printing date 17.04.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

**Trade name: DUPLI-COLOR ELOXAL SPRAY various colours**

(Contd. of page 7)

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· **Eye/face protection**



Tightly sealed goggles

· **Body protection:** Light weight protective clothing

### SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· <b>Physical state</b>	Aerosol
· <b>Colour:</b>	According to product specification
· <b>Odour:</b>	Characteristic
· <b>Odour threshold:</b>	Not determined.
· <b>Melting point/freezing point:</b>	Undetermined.
· <b>Boiling point or initial boiling point and boiling range</b>	Not applicable, as aerosol.
· <b>Flammability</b>	Not applicable.
· <b>Lower and upper explosion limit</b>	
· <b>Lower:</b>	1.2 Vol % (123-86-4 n-butyl acetate)
· <b>Upper:</b>	26.2 Vol % (115-10-6 dimethyl ether)
· <b>Flash point:</b>	Not applicable, as aerosol.
· <b>Auto-ignition temperature:</b>	240 °C (464 °F) (115-10-6 dimethyl ether)
· <b>Decomposition temperature:</b>	Not determined.
· <b>pH</b>	Mixture is non-soluble (in water).
· <b>Viscosity:</b>	
· <b>Kinematic viscosity</b>	Not determined.
· <b>Dynamic:</b>	Not determined.
· <b>Solubility</b>	
· <b>water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
· <b>Vapour pressure at 20 °C (68 °F):</b>	8300 hPa (6225.5 mm Hg) (74-98-6 propane)
· <b>Vapour pressure at 50 °C (122 °F):</b>	16500 hPa (12376 mm Hg)
· <b>Density and/or relative density</b>	
· <b>Density at 20 °C (68 °F):</b>	0.7 g/cm <sup>3</sup> (5.8 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.

· **9.2 Other information**

· <b>Appearance:</b>	
· <b>Form:</b>	Aerosol
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Explosive properties:</b>	Not determined.
· <b>Solvent content:</b>	
· <b>Organic solvents:</b>	91.3 %
· <b>VOC (EC)</b>	---
	690.0 g/l
· <b>VOC-EU%</b>	93.00 %
· <b>Solids content:</b>	8.0 %

(Contd. on page 9)

# Safety data sheet

## according to UK REACH

Printing date 17.04.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

Trade name: **DUPLI-COLOR ELOXAL SPRAY** various colours

(Contd. of page 8)

· <b>Change in condition</b>	
· <b>Evaporation rate</b>	Not applicable.
· <b>Information with regard to physical hazard classes</b>	
· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Extremely flammable aerosol. Pressurised container: May burst if heated.
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Void
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

##### 67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	>15800 mg/kg (rabbit)
Inhalative	LC50 / 4h	76 mg/l (rat)
	LC50 / 96 h	5540 mg/l (oncorhynchus mykiss)

##### 123-86-4 n-butyl acetate

Oral	LD50	10800 mg/kg (rat) (OECD 401)
Dermal	LD50	>17600 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>21 mg/m <sup>3</sup> (rat)

##### 108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8530 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>10000 mg/m <sup>3</sup> (rat)

(Contd. on page 10)

# Safety data sheet according to UK REACH

Printing date 17.04.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

**Trade name: DUPLI-COLOR ELOXAL SPRAY various colours**

(Contd. of page 9)

**reaction mass of ethylbenzene and xylene**

Oral	LD50	3523 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	29000 mg/m <sup>3</sup> (rat)

**64-17-5 ethanol**

Oral	LD50	10470 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50 / 4h	120 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information**· **12.1 Toxicity**· **Aquatic toxicity:****67-64-1 acetone**

LC50/96h	8300 mg/l (fish)
EC50/96h	7200 mg/l (algae)
LC50 / 48 h	8450 mg/l (crustacean (water flea))

**115-10-6 dimethyl ether**

EC50 / 96 h	155 mg/l (algae)
LC50 / 48 h	>4000 mg/l (daphnia magna)
LC50 / 96 h	>4000 mg/l (fish)

**108-65-6 2-methoxy-1-methylethyl acetate**

EC50 / 48 h	>500 mg/l (daphnia magna)
LC50 / 96 h	100-180 mg/l (oncorhynchus mykiss)

**reaction mass of ethylbenzene and xylene**

EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50 / 96 h	13.5 mg/l (fish)

**64-17-5 ethanol**

LC50/96h	13000 mg/l (oncorhynchus mykiss)
EC50 / 48 h	12900 mg/l (algae)
LC50 / 48 h	12340 mg/l (daphnia magna)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
- The product does not contain substances with endocrine disrupting properties.

(Contd. on page 11)

GB

## Safety data sheet according to UK REACH

Printing date 17.04.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

**Trade name: DUPLI-COLOR ELOXAL SPRAY various colours**

(Contd. of page 10)

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:**

Dispose of packaging according to regulations on the disposal of packagings.

Non contaminated packagings may be recycled.

### SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA**

UN1950

· **14.2 UN proper shipping name**

· **ADR**

1950 AEROSOLS

· **IMDG**

AEROSOLS

· **IATA**

AEROSOLS, flammable

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class**

2.5F Gases.

· **Label**

2.1

· **IMDG, IATA**



· **Class**

2.1 Gases.

· **Label**

2.1

· **14.4 Packing group**

· **ADR, IMDG, IATA**

not regulated

· **14.5 Environmental hazards:**

Not applicable.

· **14.6 Special precautions for user**

Warning: Gases.

· **Hazard identification number (Kemler code):**

-

· **EMS Number:**

F-D,S-U

(Contd. on page 12)

GB

## Safety data sheet according to UK REACH

Printing date 17.04.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

**Trade name: DUPLI-COLOR ELOXAL SPRAY various colours**

(Contd. of page 11)

· <b>Stowage Code</b>	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· <b>Segregation Code</b>	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1

\*

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· <b>Regulated explosives precursors</b>
--

None of the ingredients is listed.
------------------------------------

· <b>Regulated poisons</b>
----------------------------

None of the ingredients is listed.
------------------------------------

· <b>Reportable explosives precursors</b>
---

67-64-1	acetone	Listed
---------	---------	--------

7429-90-5	aluminium powder (stabilised)	Listed
-----------	-------------------------------	--------

· <b>Reportable poisons</b>
-----------------------------

None of the ingredients is listed.
------------------------------------

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **Seveso category P3a** FLAMMABLE AEROSOLS

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

- **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Information about limitation of use:** Employment restrictions concerning juveniles must be observed.

(Contd. on page 13)

## Safety data sheet according to UK REACH

Printing date 17.04.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

**Trade name: DUPLI-COLOR ELOXAL SPRAY various colours**

(Contd. of page 12)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H201 Explosive; mass explosion hazard.
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· **Classification according to Regulation (EC) No 1272/2008**

Data is based on internal technical data and technical data from suppliers.

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (UK REACH)
- PNEC: Predicted No-Effect Concentration (UK REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Expl. 1.1: Explosives – Division 1.1
- Flam. Gas 1A: Flammable gases – Category 1A
- Aerosol 1: Aerosols – Category 1
- Press. Gas (Comp.): Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Carc. 2: Carcinogenicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1

· **\* Data compared to the previous version altered.**

GB