

Safety data sheet
according to UK REACH

Printing date 14.04.2025

Version number 9 (replaces version 8)

Revision: 14.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name:** DUPLI-COLOR COLOR SPECIAL METAL gold

· **Article number:** 585074, 640599, 683824, 236990alt, 684982alt, 719622alt, 748899alt

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Sector of Use**

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Product category** PC9a Coatings and paints, thinners, paint removers

· **Process category**

PROC7 Industrial spraying

PROC11 Non industrial spraying

· **Application of the substance / the mixture** Lacquer

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

European Aerosols GmbH*

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@europaean-aerosols.com

European Aerosols Ltd.

Wilberforce House

Station Road

London NW4 4QE,

phone no. +44 1223 790332

*Formerly known as Motip Dupli GmbH

· **Further information obtainable from:** Department Product Safety

· **1.4 Emergency telephone number:**

Tel.: +49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergency phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland:

Poison center if child has been poisoned: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

GB

(Contd. on page 2)

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 9 (replaces version 8)

Revision: 14.04.2025

Trade name: **DUPLI-COLOR COLOR SPECIAL METAL gold**

(Contd. of page 1)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

- Hazard pictograms



GHS02



GHS07



GHS08



GHS09

- Signal word *Danger*

- Hazard-determining components of labelling:

Hydrocarbons, C9, aromatics
reaction mass of ethylbenzene and xylene

- Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

- Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P280 Wear protective gloves / eye protection.

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 9 (replaces version 8)

Revision: 14.04.2025

Trade name: DUPLI-COLOR COLOR SPECIAL METAL gold

(Contd. of page 2)

- P284 In case of inadequate ventilation wear respiratory protection.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents / container in accordance with regional regulations.

• **Additional information:**

Buildup of explosive mixtures possible without sufficient ventilation.

• **2.3 Other hazards**

• **Results of PBT and vPvB assessment**

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

• **3.2 Mixtures**

• **Description:** Mixture of substances listed below with nonhazardous additions.

• **Dangerous components:**

CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	25-<50%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	20-<25%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ STOT SE 3, H335-H336 EUH066	20-<25%
EC number: 905-588-0 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	reaction mass of ethylbenzene and xylene ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	12.5-<20%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 7440-50-8 EINECS: 231-159-6 Reg.nr.: 01-2119480154-42	copper ⚠ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10) ⚠ Acute Tox. 4, H302	2.5-<5%
CAS: 7440-66-6 EINECS: 231-175-3 Index number: 030-001-01-9 Reg.nr.: 01-2119467174-37	zinc powder -zinc dust (stabilized) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.25-<2.5%

• **Additional information:**

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

xylene: Contains ethylbenzene CAS 100-41-4

For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 9 (replaces version 8)

Revision: 14.04.2025

Trade name: **DUPLI-COLOR COLOR SPECIAL METAL gold**

(Contd. of page 3)

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters -**
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 9 (replaces version 8)

Revision: 14.04.2025

Trade name: DUPLI-COLOR COLOR SPECIAL METAL gold

(Contd. of page 4)

- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm
Long-term value: 1450 mg/m³, 600 ppm
Carc (if more than 0.1% of buta-1.3-diene)

reaction mass of ethylbenzene and xylene

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

· **DNELs**

Hydrocarbons, C9, aromatics

Oral DNEL 11 mg/kg /per day (Consumer, longterm systemic)

Dermal DNEL 25 mg/kg /per day (Worker, longterm systemic)

DNEL 11 mg/kg /per day (Consumer, longterm systemic)

Inhalative DNEL 150 mg/m³ (Worker, longterm systemic)

DNEL 32 mg/m³ (Consumer, longterm systemic)

reaction mass of ethylbenzene and xylene

Oral DNEL 1.6 mg/kg /per day (Consumer, longterm systemic)

Dermal DNEL 180 mg/kg /per day (Worker, longterm systemic)

Inhalative DNEL 211 mg/m³ (Worker, longterm systemic)

DNEL 221 mg/m³ (Worker, longterm local)

DNEL 442 mg/m³ (Worker, acute systemic)

DNEL 289 mg/m³ (Worker, acute local)

DNEL 14.8 mg/m³ (Consumer, longterm systemic)

DNEL 260 mg/m³ (Consumer; acute systemic)

DNEL 65.3 mg/m³ (Consumer, longterm local)

DNEL 260 mg/m³ (Consumer, acute local)

· **Ingredients with biological limit values:**

reaction mass of ethylbenzene and xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

- **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see section 7.

- **Individual protection measures, such as personal protective equipment**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

(Contd. on page 6)

GB

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 9 (replaces version 8)

Revision: 14.04.2025

Trade name: DUPLI-COLOR COLOR SPECIAL METAL gold

(Contd. of page 5)

Avoid contact with the eyes.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· Hand protection

Protective gloves

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· Eye/face protection

Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties**· General Information****· Physical state**

Aerosol

· Colour:

According to product specification

· Odour:

Characteristic

· Odour threshold:

Not determined.

· Melting point/freezing point:

Undetermined.

· Boiling point or initial boiling point and boiling range

Not applicable, as aerosol.

· Flammability

Not applicable.

· Lower and upper explosion limit**· Lower:**

0.7 Vol % (Hydrocarbons, C9, aromatics)

· Upper:

10.9 Vol % (74-98-6 propane)

· Flash point:

Not applicable, as aerosol.

· Auto-ignition temperature:

365 °C (689 °F) (106-97-8 butane (containing < 0,1 % butadiene (203-450-8)))

· Decomposition temperature:

Not determined.

· pH

Mixture is non-soluble (in water).

· Viscosity:**· Kinematic viscosity**

Not determined.

· Dynamic:

Not determined.

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 9 (replaces version 8)

Revision: 14.04.2025

Trade name: DUPLI-COLOR COLOR SPECIAL METAL gold

(Contd. of page 6)

· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C (68 °F):	8300 hPa (6225.5 mm Hg) (74-98-6 propane)
· Vapour pressure at 50 °C (122 °F):	16500 hPa (12376 mm Hg)
· Density and/or relative density	
· Density at 20 °C (68 °F):	0.7 g/cm ³ (5.8 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information	
· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Explosive properties:	Not determined.
· Solvent content:	
· Organic solvents:	91.3 %
· VOC (EC)	---
	610.0 g/l
· VOC-EU%	90.40 %
· Solids content:	8.7 %
· Change in condition	
· Evaporation rate	Not applicable.

· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

*

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 9 (replaces version 8)

Revision: 14.04.2025

Trade name: **DUPLI-COLOR COLOR SPECIAL METAL gold**

(Contd. of page 7)

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

Hydrocarbons, C9, aromatics

Oral	LD50	>5000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2000 mg/kg (rab) (OECD 402)

reaction mass of ethylbenzene and xylene

Oral	LD50	3523 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	29000 mg/m3 (rat)

7440-66-6 zinc powder -zinc dust (stabilized)

Oral	LD50	>2000 mg/kg (rat) (OECD 401)
Inhalative	LC50 / 4 h	>5410 mg/m3 (rat) (OECD 403)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **STOT-single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **11.2 Information on other hazards**

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

Hydrocarbons, C9, aromatics

EC50 / 48 h	302 mg/l (daphnia magna)
EC50 / 72 h	2.75 mg/l (Pseudokirchneriella subcapitata)
EC50 / 96 h	9.2 mg/l (Regenbogenforelle)

reaction mass of ethylbenzene and xylene

EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50 / 96 h	13.5 mg/l (fish)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

· 12.7 Other adverse effects

- **Remark:** Very toxic for fish

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 9)

GB

Safety data sheet

according to UK REACH

Printing date 14.04.2025

Version number 9 (replaces version 8)

Revision: 14.04.2025

Trade name: **DUPLI-COLOR COLOR SPECIAL METAL gold**

(Contd. of page 8)

Also poisonous for fish and plankton in water bodies.
Very toxic for aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation:

Dispose of packaging according to regulations on the disposal of packagings.

Non contaminated packagings may be recycled.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA

UN1950

· 14.2 UN proper shipping name

· ADR

1950 AEROSOLS, MARINE POLLUTANT/
ENVIRONMENTALLY HAZARDOUS

· IMDG

AEROSOLS, MARINE POLLUTANT

· IATA

AEROSOLS, flammable

· 14.3 Transport hazard class(es)

· ADR



· Class

2 5F Gases.

· Label

2.1

· IMDG



· Class

2.1 Gases.

· Label

2.1

· IATA



· Class

2.1 Gases.

· Label

2.1

· 14.4 Packing group

· ADR, IMDG, IATA

not regulated

· 14.5 Environmental hazards:

· Marine pollutant:

Symbol (fish and tree)

· Special marking (ADR):

Symbol (fish and tree)

· 14.6 Special precautions for user

Warning: Gases.

(Contd. on page 10)

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 9 (replaces version 8)

Revision: 14.04.2025

Trade name: DUPLI-COLOR COLOR SPECIAL METAL gold

(Contd. of page 9)

· Hazard identification number (Kemler code):	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ ENVIRONMENTALLY HAZARDOUS

*

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **Seveso category**

E1 Hazardous to the Aquatic Environment

P3a FLAMMABLE AEROSOLS

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t

(Contd. on page 11)

GB

Safety data sheet according to UK REACH

Printing date 14.04.2025

Version number 9 (replaces version 8)

Revision: 14.04.2025

Trade name: **DUPLI-COLOR COLOR SPECIAL METAL gold**

(Contd. of page 10)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

Data is based on internal technical data and technical data from suppliers.

· Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (UK REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Gas 1A: Flammable gases – Category 1A
- Aerosol 1: Aerosols – Category 1
- Press. Gas (Comp.): Gases under pressure – Compressed gas
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered.**