

DUPLI-COLOR RUST EFFECT

Ord.-no.: 383588, 434099

Technical Information



Effectspray for a special rough texture with a visual appearance like rust. If you undercoat selective areas with orange or black paint, you can achieve very individual effects. Suitable for indoor and outdoor objects. For the demands of DIY, decoration and handicraft. Suitable for metal, wood, glass, stone, ceramics, carton and many coatable plastics.

Quality & properties

- High-quality special paint
- Special, rough texture
- Very good coverage
- Excellent adherence
- Quick-drying
- Excellent colour retention: weather-resistant, light-proof, UV-resistant
- Can be recoated well

Physical & chemical data

- Base: Special resin
- Colourname: brown
- Smell: Characteristic
- Efficiency:
 - ◊ 400 ML – 1.5 m²
 - ◊ 150 ML – 0.5 - 0.6 m²
- Dry to touch: 50 min
- Overcoatable: 3 h
- Surfaces: metal, wood, glass, stone, ceramics, carton and many coatable plastics
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 8300/20 bar
- Storage stability: 10 y
- Content:
 - ◊ 400 ML
 - ◊ 150 ML

How to use

- Carefully remove loose parts of old paintings and rust. Then sand and remove dust. The ground has to be clean, dry and free from fat. Apply a primer, if necessary, e.g. DUPLI-COLOR Universal Primer Prepare coatable hard plastics with DUPLI-COLOR Plastic Primer You can create individual effects by priming selective areas with orange or black paint. Cover areas not to be painted. Before use, shake the can for 2-3 minutes. Test spray to check colour-matching and compatibility at an invisible spot. Spray several thin coats in 2 minute intervals. Spray from a distance of approx. 25 cm. Best results will be achieved at temperatures around 20°C. Do not spray over synthetic paints.
- The ground has to be clean, dry and free from fat.
- Apply a primer, if necessary, e.g. DUPLI-COLOR Universal Primer Prepare coatable hard plastics with DUPLI-COLOR Plastic Primer
- You can create individual effects by priming selective areas with orange or black paint.
- Cover areas not to be painted.
- Before use, shake the can for 2-3 minutes.
- Test spray to check colour-matching and compatibility at an invisible spot.
- Spray several thin coats in 2 minute intervals. Spray from a distance of approx. 25 cm.
- Best results will be achieved at temperatures around 20°C.
- Do not spray over synthetic paints.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com