

DUPLI-COLOR Spray Putty Automotive

Ord.-no.: 409035, 409028



Technical Information

This first-class acrylic spray putty quickly and properly closes and covers little irregularities, scratches and marks from sanding at the repair spot. Results in a perfectly smooth surface for the subsequent lacquering. The DUPLI-COLOR Acrylic Spray Putty is the ideal bonding component between the presto Polyester Putty art.no. 600054 and the following top coat.

Quality & properties

- First-class acrylic spray putty
- Excellent corrosion protection
- Especially high filling power
- High coat thickness due to good stability
- Excellent adhesion
- Can be applied in several coats
- Easy to sand after a short drying time
- Good water-resistance
- Easy to spray
- Good flow, smooth surface

Physical & chemical data

- Base: Acrylic resin
- Colourname: grey
- Smell: Characteristic
- Degree of gloss: mat, 10 ±2 GU
- Efficiency:
 - ◊ 150 ML – 0.3 m²
 - ◊ 400 ML – 0.8 m²
- Dust dry: 10 min
- Completely dry: 24 h
- Overcoatable: 60 min
- Surfaces: little irregularities, scratches and marks from sanding at the repair spot
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 8300/20 bar
- Storage stability: 10 y
- Content:
 - ◊ 150 ML
 - ◊ 400 ML

How to use

- Remove dirt, fat and oil.
- Roughen resp. grind the ground with sandpaper grain 240 up to grain 360. Rough-grinded and filled areas have to be wet-sanded. Carefully remove abrasive dust.
- Test spray at an invisible spot.
- Shake the can vigorously for approx. 3 minutes.
- Spray from a distance of approx. 25 - 30 cm.
- Apply DUPLI-COLOR Spray Putty in several thin coats.
- Wait after every coat for 2 - 5 minutes and shake the can before every new spray procedure.
- After approx. 1 hour, depending on weather conditions, wet-sand with sandpaper grain 400 to grain 500. The thicker the coat, the longer the drying time.
- Continue structure of paintwork with DUPLI-COLOR Filler und DUPLI-COLOR Acryl Auto-Spray.
- Coatable with synthetic and acrylic lacquers. Do not spray over synthetic paints!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EEC in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com