

DUPLI-COLOR COLOR SPECIAL METAL

Ord.-no.: look at ordering information



Technical Information

Decorative bronze gloss in different shades like silver and gold. For handicraft works on wood, metal, glass, cardboard etc.

Quality & properties

- High-grade synthetic quality
- Long-term high coverage and filling power
- Excellent adhesion
- Good flow, smooth surface
- Quick-drying
- Suitable for use on indoor objects
- Limited resistance to abrasion and to weathering

Physical & chemical data

- Base: Alkyd resin
- Colourname:
 - ◊ silver
 - ◊ gold
 - ◊ antique gold
- Smell: Characteristic
- Degree of gloss: high gloss, >85 GU
- Efficiency:
 - ◊ 400 ML – 1.0 m²
 - ◊ 150 ML – 0.4 m²
 - ◊ 200 ML – 0.5 m²
- Dry to touch: 60 min
- Dust dry: 10 min
- Completely dry: 24 h
- Surfaces: wood, metal, glass, cardboard, plants etc
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure:
 - ◊ 6,7-8,2/20 bar
 - ◊ 8300/20 bar
- Storage stability: 10 y
- Content:
 - ◊ 400 ML
 - ◊ 150 ML
 - ◊ 200 ML

How to use

- The ground has to be clean, dry and free of fat.
- Absorbant surfaces should be primed with DUPLI-COLOR Universal Primer.
- Mask off areas not to be painted.
- Shake the can vigorously for approx. 3 minutes.
- Test spray at an invisible spot to check colour and compatibility.
- Spray several thin coats from a distance of approx. 25 cm.
- Due to technical reasons it is not possible to conserve the excellent high gloss. A coat of clear lacquer would dissolve the effect lacquer. Just renew the gloss by applying a new coat of bronze spray.
- Do not coat with acrylic lacquer - not even after curing

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolframweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com