

DUPLI-COLOR PLATINUM Colors

Ord.-no.: look at ordering information

Technical Information



With this spray paint, which offers an extremely high coverage and quick drying, DUPLI-COLOR is setting new standards. Due to wide spectrum of possible applications, this products offers a variety of new opportunities for design and handcraft works. Our premium spray paint range DUPLI-COLOR platinum comprises more than 40 satin matt and 10 high gloss shades for indoors and outdoors applications. These lacquers are excellently suitable for all DIY and handcraft works on wood, coatable hard plastics, wallpapers, canvas, metal or glass. Test our Sprayhead Set platinum (art.no. 723087). With the use of different sprayheads you can vary with the spray distance and the spray width from very fine to wide for big areas.

Quality & properties

- Extremely quick-drying, high-grade special lacquer
- Extraordinary good coverage and high efficiency: depending on colour up to double as efficient as a conventional spray paint
- A well-balanced pressure-system allows the use of other, replaceable sprayheads, which are available as separate set packagings
- Light-fast, non-yellowing
- Nealy no spray mist

Physical & chemical data

- Base: Special combi resin
- Colourname:
 - ◊ sulfur yellow
 - ◊ grey aluminium
 - ◊ traffic purple
 - ◊ traffic blue
 - ◊ leaf green
 - ◊ chocolate brown
 - ◊ pure white
 - ◊ light grey
 - ◊ jet black
 - ◊ traffic red
 - ◊ traffic yellow
 - ◊ blue lilac
 - ◊ blackberry
 - ◊ telemagenta
 - ◊ sky blue
 - ◊ white aluminium
 - ◊ cream
 - ◊ anthracite grey
 - ◊ silver grey
 - ◊ moss green
 - ◊ gentian blue
 - ◊ ice blue
 - ◊ traffic orange
 - ◊ pastel green
 - ◊ lavender
 - ◊ terracotta
 - ◊ ice green
 - ◊ lilac
 - ◊ ivory
 - ◊ papaya
 - ◊ purple red
 - ◊ light ivory
 - ◊ peach
 - ◊ ruby red
 - ◊ pineapple
 - ◊ sapphire blue
 - ◊ pastel orange
 - ◊ melon yellow
 - ◊ yellow green
 - ◊ baby blue
 - ◊ light pink
 - ◊ spring green
 - ◊ jade
 - ◊ petrol

- ◊ mandarin
 - ◊ cherry
 - ◊ royal blue
 - ◊ lemon
 - Smell: Characteristic
 - Degree of gloss:
 - ◊ semi mat, 25 ±5 GU
 - ◊ gloss, >75 GU
 - Efficiency:
 - ◊ 400 ML – 2.1 m²
 - ◊ 150 ML – 0.5 - 0.8 m²
 - Dry to touch: 10 min
 - Dust dry: 2 min
 - Completely dry: 30 min
 - Surfaces: wood, coatable hard plastics, wallpapers, canvas, metal or glass
 - Minimum Working Temperature: 10 °C
 - Maximum Working Temperature: 25 °C
 - Vapour pressure: 4000/20 bar
 - Storage stability: 10 y
 - Content:
 - ◊ 400 ML
 - ◊ 150 ML
-

How to use

- The surface has to be clean, dry and free from fat.
- Remove residues of old paintings and rust, then sand and prime if necessary. Let dry for 1 - 2 hours.
- Use Pastic Primer on plastic parts.
- Cover areas not to be painted.
- Before use, shake the can for 3 minutes.
- Test spray at an invisible spot to check colour-matching and compatibility of the lacquer.
- Spray from a distance of approx. 25 cm several thin coats.
- Do not spray over synthetic paints.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com