

## DUPLI-COLOR profi White Lacquer

Ord.-no.: 289613, 289620

### Technical Information



Universally applicable top coat for brilliant white. For painting furniture, doors, windows and repairs to walls. Can be used on metal, wood, glass, stone, ceramic, cardboard and paintable plastics.

#### Quality & properties

- High-grade acrylic quality
- Quick drying; hard surface
- Very good coverage
- Excellent adhesion on many materials
- Good flow, smooth surface
- Suitable for indoors and outdoors applications
- Weather-resistant, light-proof, UV-resistant

#### Physical & chemical data

- Base: Acrylic resin
- Colourname: white
- Smell: Characteristic
- Degree of gloss:
  - ◊ gloss, >75 GU
  - ◊ semi mat, 25 ±5 GU
- Efficiency: 400 ML – 1.0 m<sup>2</sup>
- Dry to touch: 30 min
- Dust dry: 10 min
- Completely dry: 2 h
- Overcoatable: 30 min
- Surfaces: metal, wood, glass, stone, ceramics, carton and on paintable plastics
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 8300/20 bar
- Storage stability: 10 y
- Content: 400 ML

#### How to use

- Remove rust and dirt.
- The surface has to be clean, dry and free from fat.
- If necessary, apply a primer.
- Cover areas not to be painted.
- Before use, shake the can for 2-3 minutes.
- Test spray to check colour-matching and compatibility.
- Spray: apply from a distance of approx. 25 cm several thin cross-coats.
- Do not apply on synthetic paints!
- Before application on paintable plastics use DUPLI-COLOR Plastic Primer

#### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

#### Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)  
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)