

## DUPLI-COLOR GRANITE LOOK

Ord.-no.: look at ordering information

## Technical Information



Environmental-friendly designing and embellishing. Special waterbased latex quality. Effect Spray with countless possibilities for inside and outside use. Already with one coat you receive the impressive granite stone look.

### Quality & properties

- Special, aerosol-resistant, waterbased latex quality
- Matt - coating with glossy clear lacquer is possible
- Excellent adhesion
- Light-proof, non-yellowing
- No unpleasant odour
- Can be washed off with water and soap within 30 minutes after application.

### Physical & chemical data

- Base: Acrylic resin
- Colourname:
  - ◊ almond
  - ◊ black
  - ◊ brown
  - ◊ grey
  - ◊ light grey
  - ◊ peach
  - ◊ white
- Smell: Characteristic
- Degree of gloss: high gloss, >85 GU
- Efficiency:
  - ◊ 400 ML – 0.4 m<sup>2</sup>
  - ◊ 200 ML – 0.2 m<sup>2</sup>
- Dry to touch: 24 h
- Dust dry: 1 h
- Completely dry: 24 h
- Overcoatable: 24 h
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 8300/20 bar
- Storage stability: 10 y
- Content:
  - ◊ 400 ML
  - ◊ 200 ML

### How to use

- When applying light Granit Style colours on dark surfaces pre-coat a light primer, for example DUPLI-COLOR Universal Primer. Plastic objects are recommended to be primed with DUPLI-COLOR Plastic Primer.
- If necessary slightly sand surface. Remove the dust from smoothing.
- The surface must be clean, absolutely free of grease and dry.
- Cover areas not to be painted.
- Shake the can for 3 minutes.
- Test spray at an invisible spot.
- Spraying distance approx. 30 cm several thin coats at 2 minute intervals.
- To seal and protect the granite structure it is necessary to coat after drying (24 hrs.) with DUPLI-COLOR Granit clear lacquer or one of the below mentioned varnishes (especially at exterior use), e. g. DUPLI-COLOR Zapon Spray or polystyrene-resistant DUPLI-COLOR Deco Mat clear lacquer.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labeling**

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

**As of August 18, 2022** – This release replaces all eventually earlier issued versions.

**European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)**  
**European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)**