

DUPLI-COLOR TUNING SILVER CHROME

Ord.-no.: 674570, 665493, 674761



Technical Information

High-glossy effect spray that gives a look similar to chrome to smooth surfaces. Suitable for all smooth surfaces, especially for designing rims, wheel trims, coatable plastic parts if appropriately primed.

Quality & properties

- High-grade quality lacquer with a special combination of resins
- Very good coverage
- Excellent adhesion
- Good flow
- Quick-drying
- Resistant to abrasion
- Weather-resistant, light-proof, UV-resistant
- Scratch-, shock- and impact-resistant
- Temperature-resistant up to 150°C
- Coatable

Physical & chemical data

- Base:
 - ◊ Special combi resin
 - ◊ Special combination
- Colourname: chrome
- Smell: Characteristic
- Degree of gloss: gloss, >75 GU
- Efficiency: 400 ML – 1.5 m²
- Dry to touch: 1 h
- Dust dry: 15 min
- Completely dry: 12 h
- Surfaces: metal, wood, glass, coatable hard plastics, stone
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 4000/20 bar
- Flash point:
 - ◊ unbekannt
 - ◊ n.a.
- Storage stability: 10 y
- Content:
 - ◊ 150 ML
 - ◊ 400 ML

How to use

- The ground has to be clean, dry and free from fat.
- Cover areas not to be painted.
- Before use, shake can for 3 minutes.
- Test spray at an invisible spot. Spray from a distance of 25 cm several thin coats.
- Between the layers let lift off for 5 minutes, then apply the next layer. Repeat this till the desired effect is achieved. Remark: In order to achieve the effect, a very smooth surface is necessary. Uneven surfaces should be filled, sanded and primed with a black primer, in order to grant an optimal result.
- If a primer, e.g. DUPLI-COLOR Effect Primer black is used, this has to dry for at least one hour, before the application of the effect top coat.
- A black ground is the basis and condition for an excellent Silver Chrome Effect, e.g. by priming with TUNING EFFECT PRIMER black.
- Prime coatable plastics generally with Plastic Primer, e.g. DUPLI-COLOR PLASTIC PRIMER.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 19, 2022 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolframweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com