

DUPLI-COLOR Multi Primer

Ord.-no.: 478352, 478369

Technical Information



Suited as all-purpose primer on iron, steel, zinc, aluminium, anodized aluminium, V2A steel, powder-coated components, different plastics and wood. Active corrosion protection with exceptional adhesion, heat resistance and high filling.

Quality & properties

- Based on synthetic resins
- Weather resistant
- Quick drying
- Very good adhesion
- Heat resistant up to 80°C dry heat
- Nitro thinner resistant (after through drying)

Physical & chemical data

- Base: Special resin
- Colourname:
 - ◊ grey
 - ◊ white
- Smell: Characteristic
- Efficiency: 400 ML – 1.5 - 2.0 m²
- Dry to touch: 60 min
- Dust dry: 40 min
- Overcoatable: 3-4 h
- Surfaces: plastics and wood
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 8300/20 bar
- Storage stability: 10 y
- Content: 400 ML

How to use

- Clean surfaces to be painted thoroughly with DUPLI-COLOR Degreaser art.no. 478376, then sand
- The area must be dry and free of dust and grease
- Shake can well for 3 minutes
- Carry out spray test
- 2-3 coats
- Wear an appropriate respirator (type A2/P3)

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EEC in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.