

# DUPLI-COLOR DECO MAT Clear Coat

Ord.-no.: 193262, 749285



## Technical Information

Decorativ Paint for decoration purposes, window displays, stand construction at trade fairs, shop equipment, etc. Indispensable for stand constructions, decorators, flower-arrangers etc., but also for handicraft work at home or in courses and seminars. The polystyrene-resistant paint allows to spray directly on polystyrene bowl, blocks and other forms without a previous special priming.

### Quality & properties

- Polystyrene-resistant acrylic lacquer with a special solvent
- Very good coverage
- Excellent adhesion on many materials, e.g. polystyrene, metal, wood, glass, ceramics, eternite, concrete, stone, paper, cardboard, coatable hard plastics, flowers etc.
- Good flow, smooth surface
- Dries quick and evenly
- Suitable for painting and repairing indoors and outdoors objects
- Resistant to wiping Weather-resistant, light-proof, UV-resistant Scratch-, bump- and shock-proof
- Weather-resistant, light-proof, UV-resistant
- Scratch-, bump- and shock-proof

### Physical & chemical data

- Base: Acrylic resin
- Colourname: transparent
- Smell: Characteristic
- Degree of gloss: mat, 10  $\pm$  2 GU
- Efficiency:
  - ◊ 400 ML – 1.0 m<sup>2</sup>
  - ◊ 150 ML – 0.4 m<sup>2</sup>
- Dry to touch: 30 min
- Dust dry: 10 min
- Completely dry: 24 h
- Surfaces: polystyrene, metal, wood, glass, ceramics, eternite, concrete, stone, paper, cardboard, coatable hard plastics, flowers etc.
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 4000/20 bar
- Storage stability: 10 y
- Content:
  - ◊ 400 ML
  - ◊ 150 ML

### How to use

- Remove rust and dirt.
- The ground has to be clean, dry and free from fat.
- Possibly existing old paintings and smooth surfaces have to roughened with fine sand paper.
- Mask off areas not to be painted.
- Before use, shake can for 3 minutes.
- Test spray at an invisible spot.
- Spray from a distance of approx. 25 cm several thin coats.
- Do not spray over surfaces which are painted with synthetic resin lacquer!

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EEG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)  
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)