

DUPLI-COLOR FIRNIS SPRAY ACRYLIC

Ord.-no.: look at ordering information



Technical Information

Transparent protective coating on acrylic base for thoroughly dried paintings. Applicable on wood, cardboard, stone, ceramics and many surfaces. Protects the paint coating and increases life period. Prevents the oxidation of paintable metals.

Quality & properties

- High-grade, cristal-clear acrylic protective varnish
- Excellent adhesion
- Good flow, smooth surface
- Quick-drying
- Weather-resistant, light-proof, UV-resistang
- Resistant to wiping
- After drying scratch-, bump- and shock-proof
- For interior and exterior applications

Physical & chemical data

- Base: Acrylic resin
- Colourname: transparent
- Smell: Characteristic
- Degree of gloss:
 - gloss, >75 GU
 - mat, 10 ±2 GU
- Efficiency:
 - 400 ML – 1.0 - 2.0 m²
 - 150 ML – 0.4 - 0.8 m²
- Dry to touch: 50 min
- Dust dry:
 - 10 min
 - 1 min
- Completely dry: 24 h
- Surfaces: wood, cardboard, stone, ceramics and many surfaces
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 8300/20 bar
- Storage stability: 10 y
- Content:
 - 400 ML
 - 150 ML

How to use

- The ground has to be clean, dry and free from rust and fat. Cover areas not to be painted. Before use, shake can for 3 minutes. Test spray at an invisible spot. Spray in 2 minute intervals several thin cross-coats. Spray from a distance of approx. 25 cm Important: Do not spray over surfaces which are painted with synthetic resin lacquer!
- Cover areas not to be painted.
- Before use, shake can for 3 minutes.
- Test spray at an invisible spot.
- Spray in 2 minute intervals several thin cross-coats.
- Spray from a distance of approx. 25 cm
- Important: Do not spray over surfaces which are painted with synthetic resin lacquer!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolframweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com