

DUPLI-COLOR PLASTIC PRIMER

Ord.-no.: 557163, 319686

Technical Information



DUPLI-COLOR PLASTIC PRIMER is the perfect adhesion promoter for the subsequent painting of plastic parts. Suitable for garden furniture or other objects made of hard plastic that can be painted. Can be used on the following hard plastics: PUR, PS, PA, EPDM, ABS, GRP, hard PVC. You can then paint with DUPLI-COLOR synthetic resin, NC or acrylic paint sprays.

Quality & properties

- Solvent-based product with special adhesion-promoting additives
- Quick-drying
- Suitable for indoors and outdoors applications
- Good resistance to outside influences
- Good flow, smooth surface

Physical & chemical data

- Base: Special resin
- Colourname: transparent
- Smell: Characteristic
- Efficiency:
 - ◊ 400 ML – 5 - 6 m²
 - ◊ 150 ML – 1.8 - 2.3 m²
- Overcoatable: 15 min
- Surfaces: coatable hard plastics (garden furniture)
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 8300/20 bar
- Storage stability: 10 y
- Content:
 - ◊ 400 ML
 - ◊ 150 ML

How to use

- Clean surface from dirt, fat and silicone. Evtl. sand with sandpaper grain 600. Remove abrasive dust.
- Before use, shake can for 3 minutes.
- Apply max. 2 thin layers.
- Spray from a distance of approx. 25 cm.
- After drying (approx. 15 minutes) coatable with acrylic, synthetic or nitro-combi lacquers.
- Test spray at an invisible spot.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.