

DUPLI-COLOR ELOXAL SPRAY

Ord.-no.: look at ordering information

Technical Information



A quick-drying special lacquer with excellent hiding power and extremely good weather resistance. For color-matching painting and repair of surface scratches and damages on eloxated surfaces as doors, windows, shower cabins, hifi-devices etc.

Quality & properties

- High-grade nitro-combi quality
- Matching to eloxated aluminium
- Very good coverage
- Excellent adhesion
- Good flow, smooth surface
- Quick-drying
- Suitable for indoors and outdoors applications
- Weather-resistant, light-proof, UV-resistant
- Scratch-, shock- and impact-resistant

Physical & chemical data

- Base: Nitrocombi resin
- Colourname:
 - ◊ dark bronze
 - ◊ medium bronze
 - ◊ bronze
 - ◊ silver
 - ◊ gold
- Smell: Characteristic
- Degree of gloss: semi mat, 25 ±5 GU
- Efficiency: 400 ML – 0.8 - 1.0 m²
- Dry to touch: 30 min
- Dust dry: 15 min
- Completely dry: 24 h
- Surfaces: doors, window frames, shower cubicles, hi-fi equipment etc.
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 8300/20 bar
- Storage stability: 10 y
- Content: 400 ML

How to use

- The surface has to be clean, dry and free from fat.
- If necessary, apply DUPLI-COLOR METAL PRIMER or UNIVERSAL PRIMER.
- Cover areas not to be painted.
- Before use, shake the can for 2-3 minutes.
- Test spray to check colour-matching and compatibility.
- Spray several thin coats.
- Spray from a distance of approx. 25 cm
- Best results will be achieved during temperatures around 20°C.
- Do not apply on synthetic paints!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on

Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com